

HÄFELE



www.hafeleindia.com

HOTEL ASSORTMENT

ONE ROOM ONE SPACE



Introduction

Dear Readers,

Häfele has pioneered the way interior fittings are sold across the globe for many years now. Being a German company, our foremost concern has always been to offer our customers, premium quality products at competitive prices paired with solution based services. Our strength lies in offering a holistic range of solutions for any given interior space and yet provide the much-needed focus to understand, appreciate and furnish the dynamic demands from different customer segments. As a result of this, we present to you an exclusive range of interior solutions for our Hospitality customers under Häfele's Hotel Assortment, enabling you to execute the most ideal settings within hotel rooms and other areas. Through this range we bring to you the best technology and state-of-the-art functionality for every area of a hotel room – from the main entrance, bathroom, wardrobe to the main living area – as well as solutions for other hotel areas like the lobbies, banquet halls and restaurants.

The Häfele hotel assortment makes it possible for design concepts to be consistently implemented down to the tiniest detail. Consistent designs and finishes - from the entrance door to the bathroom accessories can be adapted to the individual design concept. The hotel room is therefore presented as a stylistic unit in every respect. At the same time, the integrated Häfele hotel assortment provides more efficiency and transparency in the procurement process by means of delivery from a single source. And because the entire assortment is available worldwide, country and continent encompassing hotel concepts can be implemented quickly and without problems at any time.

The Häfele hotel assortment consists of a wide range of fitting solutions all of which can be orchestrated into an overall room impression. For Hotel room main doors, we offer you our globally reigning range of secured and easy-to-use access control solutions - Dialock. For bathroom and wardrobe doors, our range of Sliding solutions under the SLIDO brand, present versatile options with the smoothest sliding operations and highest standards of quality. Within Bathrooms, Häfele's range of bathroom fittings including faucets, showers, shower cubicle hinges etc. provide perfect harmony in design and quality.

One aspect that brings the ideal balance to a hotel room is the overall lighting within the interiors of the room. Here, Häfele specializes in planning and executing the most perfect light settings for Hotel rooms with its range of furniture lighting solutions under the LOOX brand. The range includes every option from built-in cabinet lighting to sensor controlled plinth lighting and even light-integrated mirrors for hotel bathrooms. Loox5, the fifth generation of Häfele's Lighting solutions now introduces aesthetically engineered linear profiles with integrated strip lighting that can be recessed into different furniture units like wardrobe doors or cabinet insides and lend the most harmonious light effects to the overall furniture design.

With these interior fittings for hotel rooms, Häfele's Hotel Assortment also offers interior surfaces to execute the best renditions of bar counter tops in hotel restaurants or wall-claddings across hotel lobbies etc. Our two brands, Caesarstone (Israel) and Dekton (Spain) are world leaders in quartz and porcelain surfaces respectively, and offer immense flexibility in creating different applications within hotels.

Häfele looks after customers from the project area with its own team of specialists. You can fall back on the practical experience of our experts from specifying products and planning to tendering and operation in order to safeguard your investment in the best possible way. Moreover, our optimised logistics increase your cost-effectiveness in the material supply area. We walk along with you for the entire duration of your project to provide assistance in finding a solution to all your challenges.

So, go through this detailed product guide and get in touch with us with your specific needs. We look forward to partnering with you and assisting you in every which way possible.

Jürgen Wolf

Managing Director
(Häfele South Asia)

Hafele

Reassuring Expertise



"For over 9 decades, we've been helping people make more of their homes.

Established in Germany, and now operating worldwide, we specialise in the fittings, hardware and systems that improve the way your home works. So when you choose our products as part of your new or reformed home, you know you're getting the benefit of extensive knowledge and decades of experience.

And we're still a family business, owned and managed by family members who really care about the products and service we provide. You can rely on our commitment to the

highest standards of quality and reliability, founded on a long tradition of German engineering where attention to detail is second nature.

All our home improvement ideas are built to last – day in, day out – we want you to get the very best from every corner of your home, for many years to come."


Häfele Worldwide



With its origin in 1923 in a small town named 'Nagold' from the Swabian region of Germany that nurses a passion for hardware technology, it is no surprise that Häfele has lived up to its roots through a successful presence in the architectural and furniture hardware industry for over 9 decades now. Today, Häfele's worldwide penetration includes 38 subsidiaries across Europe, America, Asia, Australia and New Zealand. With these subsidiaries and numerous other sales organisations, Häfele operates in over 150 countries. The Häfele headquarters, 4 manufacturing units and 10 sales offices are located within Germany; while 1 manufacturing unit is located at Budapest, Hungary. The company also owns one of the largest and most sophisticated warehouses in its home country. The Häfele worldwide workforce is empowered by a base of over 8100 employees.

The group services over 150,000 customers across the globe through its extensive range of hardware products and a comprehensive logistics system. In addition to this, Häfele also provides consultative services to its customers, educating and advising them about buying the correct hardware as per their requirements. With this level of market penetration and ability to handle worldwide demand, it comes as no surprise that the company is an authority in the segment of home interior solutions; what is pleasantly surprising, though, is that in spite of its size, Häfele still remains a family owned and run business with a unique, friendly and value-centric work culture which is strongly followed among all its subsidiaries.

Hafele India



 Head Office & Regional Offices

 Hafele Design Showrooms



Häfele India is a wholly-owned subsidiary of the Häfele Global network and has been operating in India since 2003 under the leadership of Mr. Jürgen Wolf (Managing Director). The ability of the company to understand the diverse Indian market has made it an authority in the field of architectural hardware, furniture and kitchen fittings and accessories. The company also has a strong presence in synergized product categories namely Home Appliances, Furniture Lighting, Sanitary and Surfaces catering to the focused demand from these industries.

The subsidiary has a strong nation-wide presence with offices in Mumbai, Pune, Ahmedabad, Bangalore, Chennai, Hyderabad, Delhi, Kolkata and Cochin. It has full-scale operations in Sri Lanka and Bangladesh with Regional offices and Design Showrooms in both the countries; and has also spread its operations to other regions of South Asia including Nepal, Bhutan and Maldives.

Häfele's design showrooms are hubs of international home interior trends and cutting edge designs presented in a world-class environment, where customers can see home solutions in their inherent applications. These showrooms function as a one-stop-shop for all home interior and improvement needs - from providing in-depth technical advice to kitchen and wardrobe designing services through a team of experts stationed at the showroom.

Häfele India services its customers with a base of over 1300 employees, a well-networked Franchise base of over 130 shops along with over 1000 dealers situated across South Asia. The subsidiary has a sophisticated Logistics centre in Mumbai along with distribution centres in Delhi, Bangalore, Kolkata and Colombo respectively.



CONTENTS

Introduction



PAGE

1-8


Entrance Door



PAGE

9-26

Bathroom Solutions



PAGE

27-58

Living Area



PAGE

59-92

Lighting Solutions



PAGE

93-142

Movable Wall & Autotec Automatic



PAGE

143-152

Surfaces



PAGE

153-161

ONE ROOM.

The Häfele hotel assortment makes it possible for design concepts to be consistently implemented down to the tiniest detail. Consistent designs and finishes. From the entrance door to the bathroom accessory. Adapted to the individual design concept. The hotel room is therefore presented as a stylistic unit in every respect, i.e. an atmospherically rounded whole. At the same time, the integrated Häfele hotel assortment provides more efficiency and transparency in the procurement process by means of delivery from a single source. And: Because the entire assortment is available worldwide, country and continent-encompassing hotel concepts can be implemented quickly and without problems at any time.

ONE PARTNER.

ONE STYLE.

Interior design in the hotel is not an end in itself, but an important marketing instrument. The signature of the designer enhances the brand profile, and is becoming increasingly important to guests when they are deciding where to stay. At the same time, operators and investors are subject to cost-effectiveness and functionality demands, and have to reconcile the design requirements with the financial framework conditions. Häfele is making it possible to fulfil both requirements to the same extent with the hotel assortment.

ONE FACE.

ONE LOOK. ALL AREAS.

Unity in the variety.


The perception of a room is not oriented to product categories. It has a uniform and essentially subliminal effect. The Häfele hotel assortment therefore consists of a wide range of fitting solutions, but also functional furnishing accessories, all of which can be orchestrated into an overall room impression. In all zones and areas. Rather than having a multitude of

equipment details with differing origin, a coordinated range of products which enhances the harmonious impression of the room awaits the guest – and makes the procurement process much easier at the same time.

BATHROOM **p. 27**

ENTRANCE **p. 9**

SURFACES **p. 153**





p. 143 MOVABLE WALL

p. 59 LIVING

360° COMPREHENSIVE HOTEL SOLUTIONS.

Many tasks. One partner. Häfele.



ONE
PARTNER.

ONE STYLE.

Häfele looks after customers from the project area with its own team of specialists. You can fall back on the practical experience of our experts from specifying products and planning to tendering and operation in order to safeguard your investment in the best possible way. Manufacturer-independent consulting and optimised logistics increase your cost-effectiveness in the material supply area. Your contact partner from Häfele is there for you to provide assistance in finding a solution to your challenges.

SMARTPHONE KEY.

That's how hotels work today: Simply open the door with your smartphone.

Häfele is providing you with trendsetting technology with Dialock. Instead of handing a room key to your guests only when they arrive at the hotel, the smartphone key makes arrival much more convenient. The guest receives access to the hotel and his room via app. No more queues when checking in and out. The guests satisfaction increases. And you also relieve the strain on your staff at reception.

Smartphone key: Convincingly easy.

Your guests receive the key code on their app before arrival. That way, the smartphone becomes the room key. Häfele establishes secure communication between the digital room key and the Dialock electronic access control system using the latest Bluetooth® technology. The door opens.

Additional services: Perfect for you and your guests.

Book a room via the app any time anywhere, check in easily, pay and check out again without having to go to reception. Häfele's cooperation partners make it possible. They integrate other customized functions into the app, such as sales-promoting offers from your hotel or individual tips for the destination of the trip.



Different generations of hotel room keys. Key / transponder / smartphone.

ADVANTAGES

- > More convenience when arriving at the hotel: The guest receives their key code on their smartphone via app.
- > The smartphone functions as a room key and simply communicates with the Dialock electronic access control system to open the hotel room door.
- > High degree of security when opening the door thanks to the latest Bluetooth® technology.
- > Book your hotel room via the app.

WITH
SELECTED
PREMIUM
PARTNERS.



STAY HEALTHY COUNTER TOP DISPENSER⁺⁺

A simple act of sanitizing your hands has become the differentiator, today, between staying healthy and becoming vulnerable to unwanted infections!

Häfele introduces a sensor-operated Sanitizer Dispenser for Counter tops that allows preventative hygiene and protection against cross-contamination, harmful microbes and infectious viruses on surfaces. The Stay-Healthy Counter top Dispensers by Häfele can be customized to include the name and logo of your brand, for seamless integration into your corporate environment.



Our innovative product design offers complete placement flexibility within your premise & provides 360° personal hygiene and sanitation for your team and customers.



The liquid disinfectant placed in the dispenser is of the highest quality, procured from WHO GMP approved sources that have been selected after rigorous quality checks and audits

■ ENERGY:



Battery Operated

■ FINISH:



Matt Stainless Steel

■ CAPACITY:



1000 ml

■ VERSIONS:

Counter top Dispenser V1.1 (without customization of LED back-lit brand logo): 305 x 140 x 465 mm (WxDxH)

Counter top Dispenser V1.2 (with customization of LED back-lit brand logo)*: 305 x 140 x 508 mm (WxDxH)

* Brand Logo customization option for this version is available subject to minimum order quantities



Counter top Dispenser (V1.1)



Counter top Dispenser (V1.2)

STAY HEALTHY FLOOR-STANDING DISPENSER⁺⁺

A simple act of sanitizing your hands has become the differentiator, today, between staying healthy and becoming vulnerable to unwanted infections!

Häfele introduces a sensor-operated Sanitizer and Anti-bacterial Wipes Floor-Standing Dispenser that allows preventative hygiene and protection against cross-contamination, harmful microbes and infectious viruses on surfaces.



Our innovative product design offers complete placement flexibility within your premise & provides 360° personal hygiene and sanitation for your team and customers.



The Häfele "Stay Healthy" Floor-Standing Dispenser also comes equipped with an Anti-bacterial Wipes dispenser to disinfect surfaces prior to use such as Workstation, Computer Screen, Key-Boards etc.



The liquid disinfectant and anti-bacterial wipes placed in the dispenser are of the highest quality, procured from WHO GMP approved sources that have been selected after rigorous quality checks and audits

Floor-Standing Dispenser V1.1 (with Liquid Disinfectant only):

VARIANTS:



1000 ml Capacity & Battery-operated



2000 ml Capacity with Power-supply

FINISHES:



Matt Stainless Steel



Laminated Wood (on special order only)

DIMENSION:

457 x 305 x 1485 mm (WxDxH)



Floor-Standing Dispenser (V1.1)

Floor-Standing Dispenser V1.2 (with Liquid Disinfectant & Anti-bacterial Wipes):

VARIANT:



1000 ml Capacity & Battery-operated

FINISHES:



Matt Stainless Steel



Laminated Wood (on special order only)

DIMENSION:

457 x 305 x 1485 mm (WxDxH)



Floor-Standing Dispenser (V1.2)

Note: The images used in this collateral are for reference purposes only.

NEW

HAFELE

Article No	Product Description
Counter Top Dispenser	
007.59.050	Counter top Dispenser - Without customization of LED back-lit brand logo For 1000ml liquid disinfectant capacity, battery operated Finish: Matt Stainless Steel Dimension (mm): 305(W) X 140 (D) X 465 (H)
007.59.051	Counter top Dispenser - With customization of LED back-lit brand logo For 1000ml liquid disinfectant capacity, battery operated Finish: Matt Stainless Steel Dimension (mm): 305(W) X 140 (D) X 508 (H)
Floor-Standing Dispenser (Without Back Cover)	
007.59.053	Floor-Standing Dispenser For 1000ml liquid disinfectant capacity, battery operated Finish: Matt Stainless Steel Dimension (mm): 457(W) X 305 (D) X 1485 (H)
007.59.055	Floor-Standing Dispenser with Bin For 1000ml liquid disinfectant capacity, battery operated Finish: Matt Stainless Steel Dimension (mm): 457(W) X 305 (D) X 1485 (H)
007.59.057	Floor-Standing Dispenser For 2000ml liquid disinfectant capacity, power supply operated Finish: Matt Stainless Steel Dimension (mm): 457(W) X 305 (D) X 1485 (H)
Floor-Standing Dispenser (With Back Cover)	
007.59.052	Floor-Standing Dispenser For 1000ml liquid disinfectant capacity, battery operated Finish: Matt Stainless Steel Dimension (mm): 457(W) X 305 (D) X 1485 (H)
007.59.054	Floor-Standing Dispenser with Bin For 1000ml liquid disinfectant capacity, battery operated Finish: Matt Stainless Steel Dimension (mm): 457(W) X 305 (D) X 1485 (H)
007.59.056	Floor-Standing Dispenser For 2000ml liquid disinfectant capacity, power supply operated Finish: Matt Stainless Steel Dimension (mm): 457(W) X 305 (D) X 1485 (H)
Chemical Disinfectant and Alcohol Wipes	
007.59.066	Chemical Disinfectant 1 Litre Bottle (MOQ: 12 Bottles)
007.59.067	Alcohol Wipes (1 pack of 80 Wipes) (MOQ: 32 packs)

NEW

HÄFELE

FOOT PANEL PLATE | 987.53.600


Häfele's Foot Panel Plate provides the users with a germ-free, touch-less way of exiting a premise / room. Mounted towards the bottom of the door, this foot plate offers an option to the users of pulling the door open with their foot instead of a door handle.



FEATURES

- For use on doors that are frequently operated
- Enables touch-less door operations
- Prevents spread of germs
- Made from extremely durable Stainless Steel 304
- Minimum installation height from floor: 5 mm
- Maximum door load capacity: 50 kg
- Suitable for installation on timber, steel and aluminum framed doors
- For use with single swing doors or doors installed with deadbolt lock
- Hassle-free installation

TECHNICAL SPECIFICATIONS



Disclaimer: The images shown here are only for reference. The actual product and finish might differ.

Entrance door


PAGE

9



Entrance door – Product overview

**DT 700
DOOR TERMINAL SET**



**DT 710
DOOR TERMINAL SET**



**ENERGY CONTROL
TERMINAL**



**MORTICE LOCK,
PROFILE CYLINDER**



BUTT HINGE



DOOR GUARD



**CONCEALED MORTICE
HINGE**



**OVERHEAD DOOR
CLOSER, CONCEALED**



**OVERHEAD DOOR CLOSER
WITH ARM**




FIRE RESISTANT FITTING



**FLOOR MOUNTED DOOR
STOP**




**WALL MOUNTED DOOR
STOP**



DOOR VIEWER



DOOR SEAL



**SMOKE CONTROL AND
ACOUSTIC SEAL**



FIRE SEAL



Entrance door – Product overview

KEYPAD LOCK



SOLA KEY LEVER LOCK



Häfele Dialock DT 700 Door terminal set for hotel guest room doors



In accordance with DIN standard

Connection to customer-specific hotel management software possible

Connection to Room Management Systems possible (e.g. room light and welcoming light)

Suitable for state-of-the-art IT structures (e.g. browser-based authorisation control for keys and personnel, thin client, cross-location server management, ...)

Fast updating of access authorisations for guest room doors (online + mesh network), for example

- > Version: Battery-operated, intelligent door terminal, touchless activation with Dialock key or alternatively with mobile key. Thumbturn on the inside which displays "Do not disturb" on the outside when locked. Locking is mechanical. The door can be opened without a key at any time from the inside.
- > Transponder technology: Mifare Classic
- > Degree of protection: IP20
- > Door thickness: 35–95 mm
- > Standard: Tested for fire resistance in accordance with EN 1634
- > EN 1906 (terminal)
- > EN 179 (with suitable and appropriate lever handle shape)
- > Voltage supply: 4 x 1.5 V AA



Stainless steel, satin,
G-shaped lever handle

917.64.006



Stainless steel, satin,
U-shaped lever handle

917.64.051




Stainless steel, satin,
J-shaped lever handle

917.64.008



Stainless steel, brass coloured,
G-shaped lever handle

917.64.257



Stainless steel, brass coloured,
U-shaped lever handle

917.64.258



Stainless steel, brass coloured,
J-shaped lever handle

917.64.259



Stainless steel, black,
G-shaped lever handle

917.64.200



Stainless steel, black,
U-shaped lever handle

917.64.202



Stainless steel, black,
J-shaped lever handle

917.64.204

Our Dialock specialists would be pleased to provide you with advice and planning assistance.

Catalogue numbers for the smartphone key and Guest Room Management System versions are available on request.

Supplementary products which are required for operation can be found in our Häfele Dialock catalogues.




Häfele Dialock DT 710 Door terminal set for hotel guest room doors



In accordance with DIN standard


Connection to customer-specific hotel management software possible
 Connection to Room Management Systems possible
 (e.g. room light and welcoming light)
 Suitable for state-of-the-art IT structures (e.g. browser-based
 authorisation control for keys and personnel, thin client,
 cross-location server management, ...)
 Fast updating of access authorisations for
 guest room doors (online + mesh network), for example

- > Version: Battery-operated, intelligent door terminal, touchless activation with Dialock key or alternatively with mobile key. Thumbturn on the inside which displays "Do not disturb" on the outside when locked. Locking is mechanical. The door can be opened without a key at any time from the inside.
- > Transponder technology: Mifare Classic
- > Degree of protection: IP20
- > Door thickness: 35-95 mm
- > Standard: Tested for fire resistance in accordance with EN 1634
- > EN 1906 (terminal)
- > EN 179 (with suitable and appropriate lever handle shape)
- > Voltage supply: 4 x 1.5 V AA




Stainless steel, satin,
G-shaped lever handle

917.64.000




Stainless steel, satin,
U-shaped lever handle

917.64.001




Stainless steel, satin,
J-shaped lever handle

917.64.002




Stainless steel, brass coloured,
G-shaped lever handle

917.64.251



Stainless steel, brass coloured,
U-shaped lever handle

917.64.252




Stainless steel, brass coloured,
J-shaped lever handle

917.64.253




Stainless steel, black,
G-shaped lever handle

917.64.300



Stainless steel, black,
U-shaped lever handle

917.64.302



Stainless steel, black,
J-shaped lever handle

917.64.304

Our Dialock specialists would be pleased to provide you with advice and planning assistance.

Catalogue numbers for the smartphone key and Guest Room Management System versions are available on request.

Supplementary products which are required for operation can be found in our Häfele Dialock catalogues.

Häfele Dialock Energy control terminal



Suitable for activating electrical loads in guest rooms such as lighting, TV, sockets, air conditioning.

- > Function: If there is a transponder card in the energy control terminal holder, the electrical circuits and switches are enabled. The electric circuits and switches are deactivated 20 seconds after the transponder card has been removed.
- > Transponder technology: Mifare Classic 4 Byte + 7 Byte UID
- > Certified in compliance with: FCC, EMC, SAA

Our Dialock specialists would be pleased to provide you with advice and planning assistance.

Plastic, white

40 VAC

917.91.089

Häfele Startec mortice lock, project quality PC



- > Area of application: For rebated (forend 20 mm) or flush (forend 24 mm) wooden doors, e.g. for a connecting door between guest rooms
- > Version: With key action
- > Type of locking: Prepared for profile cylinder
- > Backset: 55 mm
- > Deadbolt: 2-turn
- > Lever follower: 8 mm
- > Distance: 72 mm


For a profile cylinder with a customer-specific lock (master key), please contact your Häfele specialist adviser.



Forend: Round, stainless steel, satin

Forend width 24 mm

911.02.153



Forend: Round, stainless steel, brass coloured polished, PVD coated

Forend width 24 mm

911.25.454



Forend: Round, stainless steel, graphite black, PVD coated

Forend width 24 mm


911.25.200



Forend: Square, stainless steel, satin

Forend width 24 mm

911.02.145



Forend: Square, stainless steel, brass coloured polished, PVD coated

Forend width 24 mm

911.25.446




Forend: Square, stainless steel, graphite black, PVD coated

Forend width 24 mm


911.25.422

Häfele Startec Butt hinge model DHB 3222




Stainless steel, graphite black,
PVD coated

926.98.043



Stainless steel,
satin

926.32.160
926.32.180 (Fire Rated)



Stainless steel, brass coloured
polished, PVD coated


926.98.048

- > Area of application: For flush interior doors with wooden or steel frame
- > Dimensions: 102 x 76 mm (4" x 3")
- > Flange thickness: 3 mm
- > Knuckle q: 14 mm
- > Door weight: <120 kg
- > Installation: For DIN left and DIN right hand use



Zinc alloy,
nickel plated

911.59.046



Zinc alloy, brass coloured,
PVD coated

911.59.028



Zinc alloy, graphite black,
PVD coated

911.59.029

- > Area of application:
For inwards opening
butting wooden doors

Door guard



Cover plate and chain:
Stainless steel, housing:
Stainless steel coloured

911.59.425



Cover plate and chain:
Stainless steel, housing:
Brass coloured, PVD coated

911.59.427



Cover plate and chain:
Stainless steel, housing:
Graphite black, PVD coated

911.59.421

- > Area of application:
For inwards opening
butting wooden doors
- > Material:
Housing: Zinc alloy

Häfele Startec Concealed mortise hinge



Zinc alloy,
matt chrome plated

927.91.634



Zinc alloy,
brass coloured polished

927.91.638



Zinc alloy,
black

927.91.633

- > Area of application:
For flush wooden interior
doors
- > Door weight:
<80 kg with 2 door hinges,
≤100 kg with 3 door
hinges
- > Size: 160 mm
- > Door thickness: ≥40 mm
- > Opening angle: 180°
- > Installation: For DIN left
and DIN right hand use
- > Continuously 3D adjust-
able

Häfele Startec DCL 33 Overhead door closer, concealed



- > Area of application: Tested for use on single wooden doors
- > Version: Closing speed and latching action continuously adjustable
- > Closing force: 2–4
- > Door width: ≤ 1100 mm
- > Door thickness: ≥ 46 mm
- > Opening angle: $\leq 115^\circ$
- > Hold-open angle: $\leq 115^\circ$
- > Installation: For DIN left and DIN right hand use



Aluminium, silver colour lacquered


Without hold-open

function **F**

931.84.039

With hold-open function

931.84.269



Brass, polished


Without hold-open

function **F**

931.84.035

With hold-open function

931.84.238



Aluminium, black

Without hold-open

function

931.84.033

With hold-open function

931.84.233

Häfele Startec DCL 51 Overhead door closer, with arm



Aluminium, silver colour lacquered

Without hold-open

function **F**

931.84.829

With hold-open function

931.84.669



Polished brass, PVD coated

Without hold-open

function **F**

931.84.828

With hold-open function

931.84.668



Aluminium, black

Without hold-open
function

931.84.823

With hold-open function

931.84.663



- > Area of application: Tested for use on single wooden doors
- > Version: Closing speed and latching action adjustable
- > Closing force: 2–4
- > Door width: ≤ 1100 mm
- > Opening angle: $\leq 180^\circ$
- > Hold-open angle: $\leq 145^\circ$
- > Installation: For DIN left and DIN right hand use

Intumescent fire protection kit for Häfele Startec DCL door closers

Note

The installation must comply with specifications and testing must have been carried out in accordance with EN 1634 in order to guarantee the fire resisting properties of the door. The applicable national and international guidelines, standards, approvals and other relevant regulations with regard to smoke control and fire resistance also have to be taken into consideration. Insulation against heat transfer is provided as soon as the intumescent material is activated. Concealed, hydraulic door closers must not be fitted to fire resistant doors without appropriate protection measures being taken. This is because:

- > **During installation it is required to cut away a large portion of the door which immediately reduces fire resistance.**
- > **Many models contain flammable hydraulic oil.**
- > **They are made from materials which are very good heat conductors.**
- > **The aluminium housings are likely to melt in intense heat leading to breach.**
- > **They take up much of the available door leaf thickness.**



C = intumescent fire protection kit for DCL concealed door closers


- > **Function:** The material expands substantially when exposed to hot temperatures to protect door closers, provides fire resistance of up to 60 minutes and replaces intumescent wood putty or paste
- > **Material thickness:** 2 mm

For overhead door closer, concealed

DCL 33, fire resistance 60 min
DCL 34, fire resistance 30 min

950.11.123
950.11.124

Intumescent fire protection kit for door hinges



A = intumescent fire protection kit for door hinges

- > **Function:** The material expands substantially when exposed to hot temperatures to protect door hinges, provides fire resistance of up to 60 minutes and replaces intumescent wood putty or paste
- > **Dimensions:** 102 x 30 x 2 mm

950.11.087

Floor mounted door stop



Satin
stainless steel

937.55.140



Stainless steel, brass coloured,
PVD coated

937.55.148



Stainless steel, graphite black,
PVD coated

937.55.144


- > Version: With mandrel for additional fixing in floor, suitable for entrance doors
- > Dimensions:
Diameter 44 mm
Mandrel: q 6 mm,
length 16 mm
Shoe 3.5 mm
Rubber 5 mm
- > Installation: For screw fixing

Wall mounted door stop



Satin
stainless steel

937.13.550



Stainless steel, brass coloured,
PVD coated

937.13.558



Stainless steel, graphite black,
PVD coated

937.13.553

- > Version:
With limiting bolt for coat hanger
- > Length: 82 mm
- > Buffer: q 19 mm
- > Installation: For screw fixing

Häfele Startec Door viewer



Brass, chrome plated

959.00.042



Brass, polished

959.00.048




Brass, black

959.00.121

- > Version: Fire protection tested for 60 min
- > Vision: 200°
- > For door thickness: 35–60 mm
- > Drill hole \varnothing : 14 mm
- > With cover on the inside

Door Seals




Automatic Door Bottom Seal Concealed seal for swing doors

- > Finish: Satin aluminium (durable anodised finish)
- > Sealmaterial: Silicon rubber (self extinguishing)
- > Withstands temperatures as high as 200°C
- > Approvals: Acoustic, Fire & Smoke, Energy FRL & FRR /240/60 and FD240
- > Globally certified product
- > Testingcycle: Tested to over 1,000,000 operating cycles
- > Application: Fully Mortised on single and double butt hinged door
- > Ideal for residential and light commercial applications

PVC, brown

Seal Size 600 mm, cut to size 380 mm	950.06.305
Seal Size 820 mm, cut to size 600 mm	950.06.304
Seal Size 920 mm, cut to size 820 mm	950.06.301
Seal Size 1070 mm, cut to size 920 mm	950.06.302
Seal Size 1220 mm, cut to size 1070 mm	950.06.303

Door Seals



Reversible Acoustic Door Bottom Seal Fully mortise reversible seal

- > Finish: Satin clear (durable anodised finish)
- > Seal material: Silicon rubber and aluminium (self extinguishing)
- > Silicon rubber with stands temperatures as high as 200°C. Aircraftquality aluminium
- > Approvals: Acoustic, Fire & Smoke, Energy FRL & FRR -/240/60 and FD240
- > Globally certified product
- > Testing cycle: Tested to over 1,000,000 operating cycles
- > Application: Fully Mortised on single and double butt hinged door, minimum door thickness 45mm
- > Ideal for butt hinged doors with large gaps, where internal access-ramps are used and large clearances are necessary

PVC, brown

Seal Size 920 mm, cut to size 610 mm	950.49.701
Seal Size 1070 mm, cut to size 920 mm	950.49.702

Smoke control and acoustic seal



PVC, brown

Width 12 mm, length 1000 mm

Width 12 mm, length 4200 mm

950.11.131

950.06.323

- > Area of application: For wooden doors, for sealing the air gap between the edges of door leaves and frames
- > **Smoke control and acoustic seal**
- > Sound proofing value: 31 dB
- > Smoke up to 200 °C
- > Installation: Self-adhesive

Fire seal



Sodium silicate, dark brown

Width 10 mm, fire resistance 30 min

Width 10 mm, fire resistance 60 min

950.11.031

950.06.601

- > Area of application: For wooden doors, for sealing the air gap between the edges of door leaves and frames
- > **Fire seal only**
- > Version: The material expands substantially when exposed to hot temperatures
- > Length: As required
- > Installation: Self-adhesive

Note

The installation must comply with specifications and testing must have been carried out in accordance with EN 1634 in order to guarantee the fire resisting properties of the door. The applicable national and international guidelines, standards, approvals and other relevant regulations with regard to smoke control and fire resistance also have to be taken into consideration.

Insulation against heat transfer is provided as soon as the intumescent material is activated.

Concealed, hydraulic door closers must not be fitted to fire resistant doors without appropriate protection measures being taken. This is because:

- > **During installation it is required to cut away a large portion of the door which immediately reduces fire resistance.**
- > **Many models contain flammable hydraulic oil.**
- > **They are made from materials which are very good heat conductors.**
- > **The aluminium housings are likely to melt in intense heat leading to breach.**
- > **They take up much of the available door leaf thickness.**

Keypad Lock with Motorised Latch



- > Material : Zinc Alloy
- > Finish : Satin Nickel
- > Door Thickness : 17 – 22 mm
- > Interface : Keypad Operation
- > Body Orientation : Standard Body With Pull Handle
- > Additional Protection : Tamper guard
- > Indicators : Visual & Audible usage indicators
- > Installation : Recessed or Surface Mounted
- > Power : 4 premium AA batteries
- > Battery Life : 3-5 year battery life
- > Warranty : 2 years
- > Ratings : IP 55
- > Application: Most suited for Spa's and Fitness centre

Keypad Lock

Motorised Latch Mechanism

231.98.110

Sola Key Managed Cam Lever Lock



- > Material : Zinc Alloy
- > Finish : Satin Nickel
- > Door Thickness : 10– 19 mm
- > Interface : Keypad Operation
- > Body Orientation : Vertical Body
- > Cam Operation : 90° (Top, Bottom, Left or Right)
- > Additional Protection : Tamper guard
- > Indicators : Visual & Audible usage indicators
- > Installation : Surface Mounted
- > Power : 2 Premium AA A batteries
- > Battery Life : 3-5 year battery life
- > Warranty : 2 years
- > Ratings : IP 55

Key Managed Lock

Cam Lever Mechanism

231.98.100



- > Material : Zinc Alloy
- > Finish : Satin Nickel
- > Door Thickness : 10– 19 mm
- > Interface : Keypad Operation
- > Body Orientation : Vertical Body
- > Cam Operation : 90° (Top, Bottom, Left or Right)
- > Additional Protection : Tamper guard
- > Indicators : Visual & Audible usage indicators
- > Installation : Surface Mounted
- > Power : 2 Premium AA A batteries
- > Battery Life : 3-5 year battery life
- > Warranty : 2 years
- > Ratings : IP 55

Key Managed Lock


Cam Lever Mechanism

231.98.151




Bathroom solution– Product overview


**2171 ROOM DOOR LEVER
HANDLE SET**




2170 LEVER HANDLE SET




2176 LEVER HANDLE SET



MORTICE LOCK



**MORTICE LOCK,
BATHROOM/WC FOR
WOODEN SLIDING DOORS**



**MORTICE LOCK, PC FOR
WOODEN SLIDING DOORS**



THUMBTURN CYLINDER



PC ESCUTCHEON



**WALL MOUNTED DOOR
STOP**



**DOOR HANDLE,
FOR SLIDING DOORS**



**FLUSH PULL HANDLE,
FOR WOODEN DOORS**




**FLUSH PULL HANDLE,
FOR WOODEN DOORS**



**FLUSH PULL HANDLE,
FOR WOODEN DOORS**




FLUSH PULL HANDLE



SHOWER PULL HANDLE



SHOWER DOOR KNOB



Bathroom door – Product overview

SHOWER DOOR HINGE



GLASS HOLDER FOR WALL



SHOWER DOOR HINGE



GLASS HOLDER FOR GLASS




GLASS DOOR SEAL



STABILISING ROD



CLOTHES LINE



SERIES CAESARY BLACK




SERIES SUBSIDIARY



SERIES RENOIR



Häfele Startec LDH 2171 Room door lever handle set




PC set




Satin stainless steel

903.92.556



Stainless steel, brass coloured

903.92.558



Stainless steel, graphite black

903.92.559

- > For door thickness:
38-55 mm
- > Substructure: Metal
- > Bearing: Lever handle
pivot-fitted in rose, sprung

Häfele Startec LDH 2170 Room door lever handle set

PC set



Satin stainless steel

903.92.586



Stainless steel, brass coloured

903.92.585



Stainless steel, graphite black

903.92.588

- > For door thickness: 38-55 mm
- > Substructure: Metal
- > Bearing: Lever handle pivot-fitted in rose, sprung


Häfele Startec LDH 2176 Room door lever handle set

PC set




Satin stainless steel

903.92.616



Stainless steel, brass coloured

903.92.589



Stainless steel, graphite black

903.92.583

- > For door thickness: 38-55 mm
- > Substructure: Metal
- > Bearing: Lever handle pivot-fitted in rose, sprung



Häfele Startec mortice lock, project quality bathroom/WC



Square forend, stainless steel, satin brushed

Forend width 24 mm **911.02.149**



Square forend, stainless steel, graphite black, PVD coated

Forend width 24 mm **911.25.432**



Square forend, stainless steel, brass coloured, PVD coated

Forend width 24 mm **911.25.450**


- > Area of application: For rebated (forend 20 mm) or flush (forend 24 mm) wooden doors
- > Type of locking: For bathroom/WC hinged doors
- > Backset: 55 mm
- > Deadbolt: 1-turn
- > Lever follower: 8 mm
- > Deadbolt follower: 8 mm
- > Distance: 78 mm

Mortice lock, bathroom/WC for wooden sliding doors



Zinc alloy, nickel plated

911.26.523



Zinc alloy, brass coloured, PVD coated

911.26.527



Zinc alloy, graphite black, PVD coated

911.26.522

- > Type of locking: For bathroom/WC wooden sliding doors
- > Backset: 50 mm
- > Deadbolt follower: 8 mm
- > Forend: Round, 16 mm wide
- > For door thickness: max. 45 mm (square spindle 3 and 9 mm can be shortened)

Mortice lock, PC for wooden sliding doors



Satin stainless steel

911.26.322



Stainless steel, brass coloured
PVD coated

911.26.367



Stainless steel, black,
PVD coated

911.26.368

- > Type of locking: Prepared for profile cylinder
- > Backset: 55 mm
- > Forend: Round, 20 mm wide

Thumbturn cylinder



Brass, nickel plated

Dim. A 30.5 mm, dim. B 30.5 mm, dim. C 61 mm
Dim. A 35.5 mm, dim. B 35.5 mm, dim. C 71 mm

916.96.406

916.96.416



Brass, brass coloured, PVD coated

Dim. A 30.5 mm, dim. B 30.5 mm, dim. C 61 mm
Dim. A 35.5 mm, dim. B 35.5 mm, dim. C 71 mm

916.91.953

916.91.955




Brass, graphite black, PVD coated

Dim. A 30.5 mm, dim. B 30.5 mm, dim. C 61 mm
Dim. A 35.5 mm, dim. B 35.5 mm, dim. C 71 mm

916.91.930

916.91.932



> Type of locking: WC lock
with emergency opening


PC escutcheon



PC escutcheon

Satin stainless steel


903.99.664



PC escutcheon

Stainless steel, brass coloured, PVD coated

902.52.173



PC escutcheon

Stainless steel, graphite black, PVD coated

902.52.179

> Area of application: For covering profile cylinder hole
on wooden doors
> q: 53.5 mm
> Thickness: 8 mm
> Door thickness: 38–55 mm

Wall mounted door stop



Satin stainless steel

937.13.550



Polished stainless steel

937.13.551



Stainless steel, brass coloured
PVD coated

937.13.558



Stainless steel,
graphite black, PVD coated

937.13.553


- > Version: With limiting bolts for coat hangers
- > Length: 82 mm
- > Buffer: q 19 mm
- > Installation: For screw fixing

Door handle, for sliding doors



Satin stainless steel

903.00.980



Stainless steel, brass coloured

903.00.988



Stainless steel, graphite black

903.00.983

Square – modern, puristic


- > Area of application:
For wooden and glass doors
- > Dimensions:
600 x 400 x 25 mm
- > For door thickness:
8-50 mm
- > Installation: For 13 mm or 8.5 mm drill hole (glass/wood), for screw fixing with M8 x 40 mm, M8 x 80 mm threaded bolt + rubber layer for glass

Round – classic, timeless



Satin stainless steel

903.06.030



Stainless steel, brass coloured

903.06.038



Stainless steel, graphite black

903.06.033

- > Area of application:
For wooden and glass doors
- > Dimensions:
600 x 400 x 25 mm
- > For door thickness:
8-50 mm
- > Installation: For 13 mm or 8.5 mm drill hole (glass/wood), for screw fixing with M8 x 40 mm, M8 x 80 mm threaded bolt + rubber layer for glass



Flush pull handle, for wooden doors



Stainless steel,
satin brushed

155.01.495



Stainless steel, brass coloured,
PVD coated

151.38.120



Stainless steel, graphite black,
PVD coated

151.38.121

Square

> Dimensions:
140 x 45 x 13 mm

Flush pull handle, for wooden doors



Satin stainless steel

q 50 mm	155.01.490
q 60 mm	155.01.491



Stainless steel, brass coloured

q 50 mm	151.38.100
q 60 mm	151.38.101



Stainless steel, black

q 50 mm	151.38.102
q 60 mm	151.38.103


Round

> Thickness: 15 mm



Stainless steel,
satin brushed

155.01.505



Stainless steel, brass coloured,
PVD coated

151.38.110



Stainless steel, graphite black,
PVD coated

151.38.111

Oval

> Dimensions:
130 x 37 x 13 mm

Flush pull handle, for glass doors

Square – modern, puristic



Satin stainless steel

981.52.570



Polished stainless steel

981.52.571




Stainless steel, graphite black,
PVD coated

981.52.573

- > Dimensions:
70 x 70 mm
- > For glass thickness:
8-12 mm
- > Glass drilling: 50 mm

Round – classic, timeless



Satin stainless steel

981.52.520



Polished stainless steel

981.52.521



Stainless steel, graphite black,
PVD coated

981.52.523

- > q: 60 mm
- > For glass thickness:
8-12.7 mm
- > Glass drilling: 48 mm

Flush pull handle, for glass doors

Square – modern, puristic



Satin stainless steel

981.20.140



Polished stainless steel

981.20.141



Stainless steel, graphite black, PVD coated

981.52.583

- > Dimensions:
70 x 70 mm
- > For glass thickness:
8-12 mm
- > Glass drilling: 50 mm

Round – classic, timeless



Satin stainless steel

981.52.530



Polished stainless steel

981.52.531



Stainless steel, graphite black, PVD coated

981.52.533

- > q: 60 mm
- > For glass thickness:
8-12.7 mm
- > Glass drilling: 48 mm

Shower door handle with towel rail



Square – modern, puristic



Polished stainless steel

200 x 450 mm **981.77.003**
300 x 500 mm **981.77.004**



Stainless steel, graphite black

200 x 450 mm **981.77.011**
300 x 500 mm **981.77.012**
450 x 550 mm **981.77.013**

The clear, geometric design creates emphasis in the bathroom; ergonomically designed door handle

- > Dimensions:
200/300/450 (drilling distance)
x 25 x 25 mm
(depth 70 mm) shower door handle,
450/500/550 (drilling distance)
x 25 x 25 mm
(depth 70 mm) towel rail
- > For glass thickness: 8-13.1 mm
- > Installation: For screw fixing,
glass drilling required

Round – classic, timeless



Polished stainless steel

200 x 450 mm **980.47.001**



Stainless steel, graphite black

200 x 450 mm **981.52.116**
300 x 500 mm **981.52.117**
450 x 550 mm **981.52.118**

The soft and round shape brings peace and elegance into the bathroom; ergonomically designed door handle

- > Dimensions:
200/300/450 mm (drilling distance)
(depth 70 mm) shower door handle,
450/500/550 mm (drilling distance)
(depth 70 mm) towel rail,
handle q 25 mm
- > For glass thickness: 8-13.1 mm
- > Installation: For screw fixing,
glass drilling required

Shower door handle

Square – modern, puristic



Polished stainless steel

Length 450 mm	981.77.000
Length 500 mm	981.77.001
Length 550 mm	981.77.002



Stainless steel, graphite black

Length 450 mm	981.77.008
Length 500 mm	981.77.009
Length 550 mm	981.77.010

The clear, geometric design creates emphasis in the bathroom; ergonomically designed door handle

- > Dimensions:
450/500/550 (drilling distance)
x 70 mm depth
- > Knob: . 25 x 35 mm
- > For glass thickness: 8-13.1 mm
- > Installation: For screw fixing,
glass drilling required

Round – classic, timeless



Polished stainless steel

Length 450 mm	980.47.011
Length 500 mm	981.52.104
Length 550 mm	981.52.105



Stainless steel, graphite black

Length 450 mm	981.52.113
Length 500 mm	981.52.114
Length 550 mm	981.52.115

The soft and round shape brings peace and elegance into the bathroom; ergonomically designed door handle

- > Dimensions:
450/500/550 (drilling distance)
x 70 mm depth,
handle q 25 mm
- > Knob: q 25 x 35 mm
- > For glass thickness: 8-13.1 mm
- > Installation: For screw fixing,
glass drilling required

Shower door knob

Square – modern, puristic



Polished stainless steel

981.77.006



Stainless steel, graphite black, PVD coated

981.77.014

The clear, geometric design creates emphasis in the bathroom; ergonomically designed door handle

- > Dimensions:
25 x 35 mm per knob
- > For glass thickness: 8-13.1 mm
- > Installation: For screw fixing, glass drilling required

Round – classic, timeless



Polished stainless steel

981.52.109



Stainless steel, graphite black, PVD coated

981.52.110

The soft and round shape brings peace and elegance into the bathroom; ergonomically designed door handle

- > Dimensions:
q 25 x 35 mm per knob,
knob q 25 mm
- > For glass thickness: 8-13.1 mm
- > Installation: For screw fixing, glass drilling required

Shower door hinge, for wall-glass connection



Brass,
chrome plated polished

981.51.004




Brass, graphite black,
PVD coated

981.51.003

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Glass dimensions: Door width max. 800 mm, door height max. 2400 mm
- > Dimensions: Hinge: 90 x 55 mm
Screw-on plate 90 x 50 mm
- > Load bearing capacity: Max. 45 kg
(with use of 2 shower door hinges)
- > Mounting: For DIN left and DIN right hand use
- > Opening angle: 90°
on both sides with locking mechanism in open position
- > Lock function: From an opening angle of approx. 85°
- > Installation: For screw fixing, glass cut-out required



Brass,
chrome plated polished

981.02.081




Brass, graphite black,
PVD coated

981.02.083

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Glass dimensions: Door width max. 800 mm, door height max. 2400 mm
- > Dimensions: Hinge: 90 x 55 mm
Screw-on plate 90 x 50 mm
- > Load bearing capacity: Max. 45 kg
(with use of 2 shower door hinges)
- > Mounting: For DIN left and DIN right hand use
- > Opening angle: 90°
on both sides with locking mechanism in open position
- > Lock function: From an opening angle of approx. 85°
- > Installation: For screw fixing, glass cut-out required



Glass holder for wall-glass connection



Brass,
chrome plated polished

981.02.254




Brass, graphite black,
PVD coated

981.02.253

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Dimensions: 45 x 45 mm
- > Angle: 90°
- > Mounting: For left and right hand use
- > Installation: For screw fixing, glass cut-out required



Concealed wall mounting



Brass,
chrome plated polished

981.02.263




Brass, graphite black,
PVD coated

981.02.243

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Dimensions: 45 x 45 mm
- > Angle: 90°
- > Mounting: For left and right hand use
- > Installation: For screw fixing, glass cut-out required



Shower door hinge, for glass-glass connection



Brass, chrome plated polished,
90° glass front

981.51.014




Brass, graphite black,
PVD coated, 90° glass front

981.51.013

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Glass dimensions: Door width max. 800 mm, door height max. 2400 mm
- > Dimensions: 90 x 55 mm
- > Load bearing capacity: Max. 45 kg (with use of 2 shower door hinges)
- > Mounting: For DIN left and DIN right hand use
- > Opening angle: 90° on both sides with locking mechanism in open position
- > Lock function: From an opening angle of approx. 85°
- > Installation: For screw fixing, glass cut-out required



Brass, chrome plated polished,
135° glass front

981.51.021




Brass, graphite black,
PVD coated, 135° glass front

981.51.023


The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Glass dimensions: Door width max. 800 mm, door height max. 2400 mm
- > Dimensions: 90 x 55 mm
- > Load bearing capacity: Max. 45 kg (with use of 2 shower door hinges)
- > Mounting: For DIN left and DIN right hand use
- > Opening angle: 90° on both sides with locking mechanism in open position
- > Lock function: From an opening angle of approx. 85°
- > Installation: For screw fixing, glass cut-out required



Brass, chrome plated polished,
180° glass front

981.51.031




Brass, graphite black,
PVD coated, 180° glass front


981.51.033

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Glass dimensions: Door width max. 800 mm, door height max. 2400 mm
- > Dimensions: 90 x 55 mm
- > Load bearing capacity: Max. 45 kg (with use of 2 shower door hinges)
- > Mounting: For DIN left and DIN right hand use
- > Opening angle: 90° on both sides with locking mechanism in open position
- > Lock function: From an opening angle of approx. 85°
- > Installation: For screw fixing, glass cut-out required



Glass holder, for glass-glass connection



Brass, chrome plated polished,
90° glass front

981.02.264




Brass, graphite black,
PVD coated, 90° glass front

981.02.263

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Dimensions: 45 x 45 mm
- > Angle: 90°
- > Mounting: For left and right hand use
- > Installation: For screw fixing, glass cut-out required



Brass, chrome plated polished,
135° glass front

981.02.094




Brass, graphite black,
PVD coated, 135° glass front

981.02.093

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Dimensions: 45 x 45 mm
- > Angle: 135°
- > Mounting: For left and right hand use
- > Installation: For screw fixing, glass cut-out required



Brass, chrome plated polished,
180° glass front

981.02.274




Brass, graphite black,
PVD coated, 180° glass front


981.02.273

The clear, geometric design creates emphasis in the bathroom

- > For glass thickness: 8-12 mm
- > Dimensions: 45 x 45 mm
- > Angle: 180°
- > Mounting: For left and right hand use
- > Installation: For screw fixing, glass cut-out required



Glass door seal, for shower cubicles glass-glass



PVC transparent

For wall and bottom seal for glass thickness 8 mm	950.50.409
For wall and bottom seal for glass thickness 10 mm	950.50.410
For wall and bottom seal for glass thickness 12 mm	950.50.411

- > Version:
- > Length: 2.4 m, can be shortened as required
- > Installation: For sliding onto glass edge


Glass door seal, for shower cubicles glass-wall or glass-floor



PVC transparent

For wall sealing, for glass thickness 8 mm	950.50.400
For wall sealing, for glass thickness 10 mm	950.50.401
For wall sealing, for glass thickness 12 mm	950.50.402

- > Version:
For creating a seal between shower doors and adjacent wall or floor areas
- > Length: 2.4 m, can be shortened as required
- > Installation: For sliding onto glass edge




PVC transparent

For Weather seal, for glass thickness 8 mm	950.50.403
For Weather seal, for glass thickness 10 mm	950.50.404
For Weather seal, for glass thickness 12 mm	950.50.405


- > Version:
For creating a seal between shower doors and adjacent wall or floor areas
- > Length: 2.4 m, can be shortened as required
- > Installation: For sliding onto glass edge

Magnetic glass door seal, for shower cubicles glass-glass




PVC transparent

For 90° glass fronts, for glass thickness 8 mm	950.50.412
For 90° glass fronts, for glass thickness 10 mm	950.50.413
For 90° glass fronts, for glass thickness 12 mm	950.50.414



PVC transparent

For 135° glass fronts, for glass thickness 8 mm	950.50.415
For 135° glass fronts, for glass thickness 10 mm	950.50.416
For 135° glass fronts, for glass thickness 12 mm	950.50.417



PVC transparent

For 180° glass fronts, for glass thickness 8 mm	950.50.412
For 180° glass fronts, for glass thickness 10 mm	950.50.413
For 180° glass fronts, for glass thickness 12 mm	950.50.414

- > Version:
For sealing of 2-leaf shower doors, with magnet for holding in closed position
- > Length: 2.4 m, can be shortened as required
- > Installation: For sliding onto glass edge

Note: 90° and 180° magnetic seal are same, during installation, one seal is kept ideal and other is rotated, to match the need.

Stabilising rod for shower walls, 90°




Brass, chrome plated polished

981.02.061



Brass, graphite black, PVD coated

981.02.063



- > For glass thickness: 8-12 mm
- > Length: 1050 mm
- > q: Rod 20 mm, end cap: 28 mm
- > Installation: For screw fixing (wall)/clipping on (glass)

Stabilising rod for shower walls, 45°




Brass, chrome plated polished

981.02.071



Brass, graphite black, PVD coated

981.02.073




- > For glass thickness: 8-12 mm
- > Length: 400 mm
- > q: Rod 20 mm, end cap: 28 mm
- > Installation: For screw fixing (wall)/clipping on (glass)

Clothes line



Polished stainless steel

980.60.951



Stainless steel, graphite black, PVD coated

980.60.953

All-metal, therefore extremely robust and durable; space-saving, disappears completely into housing after use

- > Version: Pull-out steel wire which can be tensioned towards receiver
- > Extension length: 2.5 m
- > Dimensions: Housing q 91 x 57 mm, receiver 65 x 35 x 9 mm

Series CAESARY BLACK

Redefining the Caesary Series with an element of “black” sophistication - because “black” is classy



Soap dish

983.23.042



Soap dispenser

983.23.132



Tumbler holder

983.23.062




Towel ring

983.23.082

Series CAESARY BLACK



Glass shelf
983.23.122



Robe Hook
983.23.092



Towel rail
983.23.022



Double towel rail
983.23.032



Multi towel rail
983.23.012



Towel rack
983.23.002

Series CAESARY BLACK



Toilet paper holder

983.23.072




Toilet brush set

983.23.112


Series SUBSIDIARY

A combination series of allied products - so that you don't miss the details



Shaving mirror

495.81.000



Shaving mirror

980.64.512

Series RENOIR

Clean lines in slim designs – delicate, even and charming



Soap dish

980.62.002



Tumbler holder

980.62.022



Soap dispenser

980.62.042



Towel ring

980.62.102

Series RENOIR



Wire Shelf (small)

980.62.012



Robe hook

980.62.132



Towel rail

980.62.112



Towel rack

980.62.122

Series RENOIR



Toilet paper holder with cover

980.62.302



Toilet Brush Set

980.62.312


Living Area

PAGE

59

Living area – Product overview

FURNITURE HANDLE



FURNITURE HANDLE



FURNITURE HANDLE




FURNITURE KNOB



HÄFELE LOOX
WARDROBE RAIL, OVAL



RAIL CENTRE SUPPORT,
OVAL



RAIL END SUPPORT,
OVAL



PIVOT HINGE FOR WRITING
BUREAU FOR SURFACES
THAT CAN BE FOLDED
DOWN



WARDROBE RAIL, ROUND




RAIL CENTRE SUPPORT,
ROUND



RAIL END SUPPORT,
ROUND



COAT HANGERS WITH
COAT HANGER RECEIVER




COAT HANGERS




WARDROBE HOOKS



PROTECTION RAILS
FOR FURNITURE ITEMS



LUGGAGE STAND



Living area – Product overview


HAFELE SAFE



MINI BAR




VENTILLATION GRILL




CONNECTING FITTING




CLASSIC 50 VF S (ST - 18)




CLASSIC IF 50




CLASSIC DUO 80 VF




CLASSIC IF 45




CLASSIC 80 W



CLASSIC 120 S



CLASSIC 100 C



HÄFELE IRONFIX IRONING BOARD



IRONING BOARD, INCL. SUPPORT



Living area – Product overview

HÄFELE DUOLETTO BUILT-IN FOLDAWAY BED



> page 87

HÄFELE TELELETTO II FOLDAWAY BED FITTING FOR SOFA BED



> page 88

KETTLE



> page 89

PEDAL BINS



> page 91

WALL MOUNTED TV BRACKET



> page 92

Furniture handle



Square – modern, puristic



Stainless steel satin, brushed, quality 1.4301

Dimensions 106 x 35, CC 96 mm

Dimensions 138 x 35, CC 128 mm

Dimensions 170 x 35, CC 160 mm


Dimensions 202 x 35, CC 192 mm

155.01.340

155.01.341

155.01.342

155.01.343




Stainless steel, brass coloured, PVD coated

Dimensions 106 x 35, CC 96 mm

Dimensions 138 x 35, CC 128 mm

112.04.080

112.04.081



Stainless steel, graphite black, PVD coated

Dimensions 106 x 35, CC 96 mm

Dimensions 138 x 35, CC 128 mm


112.04.082

112.04.083

- > Cross section: 10 x 10 mm
- > Installation: For screw fixing with threaded screw M4




Furniture handle



Stainless steel, quality 1.4301, satin brushed

Dimensions 106 x 35, CC 96 mm	155.01.231
Dimensions 138 x 35, CC 128 mm	155.01.232
Dimensions 170 x 35, CC 160 mm	155.01.233
Dimensions 202 x 35, CC 192 mm	155.01.234



Stainless steel, quality 1.4301, brass coloured polished, PVD coated

Dimensions 106 x 35, CC 96 mm	112.04.070
Dimensions 138 x 35, CC 128 mm	112.04.071




Stainless steel, quality 1.4301, graphite black, PVD coated

Dimensions 106 x 35, CC 96 mm	112.04.072
Dimensions 138 x 35, CC 128 mm	112.04.073


Round – classic, timeless

- > q: 10 mm
- > Installation: For screw fixing with threaded screw M4




Stainless steel, satin brushed

Dimensions 136 x 35, CC 96 mm	155.01.400
Dimensions 168 x 35, CC 128 mm	155.01.401
Dimensions 200 x 35, CC 160 mm	155.01.402
Dimensions 232 x 35, CC 192 mm	155.01.403



Stainless steel, brass coloured polished, PVD coated

Dimensions 136 x 35, CC 96 mm	112.04.060
Dimensions 168 x 35, CC 128 mm	112.04.061



Stainless steel, graphite black, PVD coated

Dimensions 136 x 35, CC 96 mm	112.04.062
Dimensions 168 x 35, CC 128 mm	112.04.063

- > q: Handle 12 mm, support 10 mm
- > Installation: For screw fixing with threaded screw M4

Furniture knob



Square – modern, puristic



Stainless steel,
satin brushed

12 x 12 x 25 mm **112.02.110**
20 x 20 x 30 mm **112.02.111**



Stainless steel, brass coloured
polished, PVD coated

12 x 12 x 25 mm **112.02.112**
20 x 20 x 30 mm **112.02.113**



Stainless steel, graphite black,
PVD coated

12 x 12 x 25 mm **112.02.114**
20 x 20 x 30 mm **112.02.115**

> Installation: For screw fixing with threaded screw M4

Round – classic, timeless



Stainless steel,
satin brushed

q 12 mm, L 25 mm **155.01.485**
q 20 mm, L 30 mm **155.01.486**



Stainless steel, brass coloured
polished, PVD coated

q 12 mm, L 25 mm **112.02.102**
q 20 mm, L 30 mm **112.02.103**



Stainless steel, graphite black,
PVD coated

q 12 mm, L 25 mm **112.02.104**
q 20 mm, L 30 mm **112.02.105**

> Installation: For screw fixing with threaded screw M4

Häfele Loox wardrobe rail, oval



Can be illuminated with Häfele Loox LED strip light



Aluminium, silver coloured anodized

833.72.790

- > Version: Can be illuminated with Häfele Loox LED strip light, light channel cover frosted
- > Dimensions: 30 x 15 x 2500 mm

OVA Wardrobe rail, oval



Steel, chrome plated

801.03.222

- > Dimensions: 30 x 15 x 2500 mm
- > Material thickness: 0.8 mm

Rail centre support, oval



Zinc alloy, chrome plated

Height adjustable 85–105 mm **802.07.200**



Zinc alloy, chrome plated

Rigid 75 mm **802.07.210**

- > Area of application: For OVA wardrobe rail 30 x 15 mm
- > Installation: For screw fixing beneath shelves

Rail end support, oval



Zinc alloy, nickel plated

803.33.756

- > Area of application: For OVA wardrobe rail 30 x 15 mm
- > Dimensions: 43 x 18 x 10 mm
- > Installation: For screw fixing to side panel

Pivot hinge for writing bureau for surfaces that can be folded down



Stainless steel, ground

For panel heights <400 mm,
load bearing capacity 40 kg
For panel heights <500 mm,
load bearing capacity 60 kg
For panel heights <600 mm,
load bearing capacity 70 kg

361.50.830

361.50.831

361.50.832

- > Area of application: For folding tables, additional work surfaces or luggage racks in hotels
- > Opening angle: 90°
- > Flange thickness: 5 mm
- > For panel width: <1200 mm
- > Installation: For screw fixing

Note:

The specified load bearing capacities only apply under the following conditions:

With static loads which are placed in the centre of the panel, when using dimensionally stable materials

Wardrobe rail, round



Steel, nickel plated

801.01.702

- > q: 20 mm
- > Length: 2,500 mm
- > Material thickness: 0.7 mm

Rail centre support, round



Zinc alloy, nickel plated

802.02.220

- > Area of application: For round wardrobe rail q 20 mm
- > Dimensions: 63 x 38 x 19 mm
- > Installation: For screw fixing beneath shelves

Rail end support, round



Brass, nickel plated

803.51.702

- > Version: Consists of base plate and union sleeve
- > Area of application: For round wardrobe rail q 20 mm
- > Dimensions: 28 x 12.5 mm
- > Installation: Screw base plate to side panel, screw the union sleeve which is slid onto the wardrobe rail to the base plate

Coat hangers with coat hanger receiver



Stainless steel, satin brushed, quality 1.4305

Coat hanger	804.32.050
Coat hanger receiver	804.32.059

> Area of application: For round wardrobe rail q 20 mm and oval wardrobe rail 30 mm

Coat hangers



Hardwood, natural colour lacquered

Standard
842.71.410



Hardwood, natural colour lacquered
With non-slip trouser bar and skirt notches
842.71.420



Hardwood, dark brown

Standard
842.71.100




Hardwood, dark brown
With non-slip trouser bar and skirt notches
842.71.320

> Area of application: For round wardrobe rail q 20 mm and oval wardrobe rail 30 mm


Wardrobe hooks

Square – modern, puristic




Stainless steel, satin brushed, quality 1.4301

844.28.110



Stainless steel, brass coloured polished, PVD coated

844.28.111



Stainless steel, graphite black, PVD coated

844.28.112


- > Dimensions: 42 x 14 x 35 mm
- > Installation: For screw fixing

Round – classic, timeless



Stainless steel, quality 1.4301, satin brushed

844.28.100



Stainless steel, quality 1.4301, brass coloured polished, PVD coated

844.28.101



Stainless steel, quality 1.4301, graphite black, PVD coated

844.28.102

- > Dimensions: 55 x 14 x 35 mm
- > Installation: For screw fixing

Protection rails for furniture



Zinc alloy, stainless steel coloured

Length 450 mm, self-adhesive **808.90.091**
 Length 600 mm, for screw fixing **808.90.084**



Zinc alloy, graphite black

Length 450 mm, self-adhesive **808.90.391**
 Length 600 mm, for screw fixing **808.90.384**

- > Version: One set consists of 6 protection rails
- > Dimensions: 13 x 7 mm

Luggage stand



Polished stainless steel

983.25.091

- > Version: Collapsible with elastic straps for luggage rack
- > Dimensions: 660 x 620 x 440 mm (in open position)

Hotel safe



- > Version: Motorised electronic numerical combination lock (PIN code 3-6 digits), opens upwards, with LED display, the last 100 openings can be read out via the display
- > Dimensions and weight: External dimensions 400 x 145 x 350 mm, internal dimensions 395 x 75 x 345 mm, weight 15 kg
- > Material thickness: Housing 2 mm, door 6 mm
- > Emergency opening: Using master PIN or emergency opening key

Supplied with:

1 hotel safe, 4 alkaline AA batteries, mounting accessories

Hotel safe

Steel, black

836.24.350

Data transfer unit (optional)

836.24.980

Mini bar, volume 42 litres

Peltier technology



- > Dimensions: H 508 x W 420 x D 425 mm
- > Version: 2 tiers, receptacle for 1.5 l bottles and LED interior lighting
- > Operating noise: 38 dB
- > Peltier technology: Cooling compared to room temperature 20 °C ΔT max. 6.5–15 °C
- > Nominal voltage: 110–120 V or 220–240 V, 50–60 Hz
- > Wattage: 50 W
- > Energy efficiency class: B
- > Energy consumption: 109 kWh/annum
- > Weight: 9.4 kg
- > Installation: Without front panel

Black


Schuko safety plug

Nominal voltage: 220–240 V, 50–60 Hz

US plug


568.27.257

Ventilation grill



Plastic, light grey

959.10.005



Plastic, black

959.10.006

- > Version: Two-piece, with frame, louvre type concealed ventilation slots
- > Dimensions: 457 x 92 mm
- > Cut-out: 433 x 77 mm
- > For door thickness: 35–40 mm
- > Ventilation: 200 cm²
- > Installation: For recess mounting

Installation reference for mini bars

- > At least 200 cm² fan cross-section for air supply and ventilation
- > 20 mm distance from rear of refrigerator to furniture
- > Direct connection from absorber device to ventilation duct


Connecting fitting for appliance doors



Plastic, brown

568.16.007

- > Area of application: For connecting the mini bar door with a pre-mounted furniture door
- > Installation: For screw fixing





Classic 50 VF S (ST - 18)



Vorfront sliding system for wooden wardrobe and furniture doors.

400.51.125

For 2 Doors - Sliding door kit consists of:

- > 2 Running Gears with Ball Bearing
- > 1 Running Gear for Inner Door
- > 1 Running Gear with Pins
- > 2 End Stoppers
- > 2 Bottom Guides for Inner Door
- > 2 Bottom Guides Adjustable
- > 4 Clips for Guide
- > 2 End Stops
- > 2 Support Blocks
- > Central Stop


Hardware Specification:

- > Smooth and effortless sliding doors
- > Easy installation
- > Suitable for 2 door and 3 door applications


400.51.129

For 3 Doors - Sliding door kit consists of:

- > 2 Running Gears with Ball Bearing
- > 2 Running Gears for Inner Door
- > 2 Running Gears with Pins
- > 2 End Stoppers
- > 4 Bottom Guides for Inner Door
- > 2 Bottom Guides Adjustable
- > 6 Clips for Guide
- > 2 End Stops
- > 2 Support Blocks
- > 1 Central Stop

Product Name	Article No.	
Silver anodized aluminium top track (Note: Track to be ordered separately)	400.52.026	2500 mm
	400.52.036	3500 mm
Silver anodized aluminium bottom track (Note: Track to be ordered separately)	400.52.954	2500 mm
	400.52.955	3500 mm

Classic IF 50



Infront sliding system for wooden wardrobe and furniture doors

Hardware Specification:


- > Bottom running rollers for smooth and effortless movement
- > The pre-drilled holes are oblong in shape to provide for adjustability and alignment of panels
- > The top and bottom (common) tracks are extruded anodized Aluminium profiles for smooth movement of the roller
- > Very easy to install and ensures running stability for bottom running sliding

Complete accessories set for 1 door


404.24.000

Sliding door kit consists of:

- > 2 Runners
- > 2 Bottom Guides
- > 2 End Stoppers

Product Name	Article No.	
Extruded aluminium top track (Note: Track to be ordered separately)	404.24.901	3000 mm


Classic DUO 80 VF



(Vorfront) sliding system for wooden wardrobe and furniture doors.

Hardware Specification :

- > High load capacity up to 80 kg
- > More than one adjustment
- > Door thickness 28mm & 38mm
- > Anti derailing system inside the lower slide
- > Provides easy way to mount heavy doors onto the furniture with just a clack
- > Adjustment: +3mm/-3mm (vertical adjustment)
- > Soft Closing: opening and closing

Product Name	Article No.	
Silver anodized aluminium top track (Note: Track to be ordered separately)	409.36.606	3000 mm
	409.36.604	3600 mm
Silver anodized aluminium bottom track (Note: Track to be ordered separately)	400.50.936	3000 mm
	400.50.804	3600 mm
Kit straightener (optional)	400.50.011	

Classic DUO 80 VF

409.36.112

For Door Thickness of 28 mm

External door kit consists of:

- > 2 Steel Adjustable Upper Slide
- > 2 Steel Lower Slide with Wheel and O-Ring
- > 1 Right Plastic Adjustable Upper Lock
- > 1 Left Plastic Adjustable Upper Lock
- > 1 Plastic Upper Central Lock.
- > 2 Plastic Lower Lock
- > 1 Rounded Socket Key with 4 mm Hexagonal Ends

409.36.110

> For Door Thickness of 38 mm

> External door kit consists of:

- > 2 Steel Adjustable Upper Slide
- > 2 Steel Lower Slide with Wheel and O-Ring
- > 1 Right Plastic Adjustable Upper Lock
- > 1 Left Plastic Adjustable Upper Lock
- > 1 Plastic Upper Central Lock.
- > 2 Plastic Lower Lock
- > 1 Rounded Socket Key with 4 mm Hexagonal Ends

409.36.111

Internal door kit consists of:

- > 2 Steel Adjustable Upper Slide
- > 2 Steel Lower Slide with Wheel and O-Ring
- > 1 Right Plastic Adjustable Upper Lock
- > 1 Left Plastic Adjustable Upper Lock
- > 1 Plastic Upper Central Lock.
- > 2 Plastic Lower Lock
- > 1 Rounded Socket Key with 4 mm Hexagonal Ends



SOFTSPACE Device For External & Internal Door (Note: Available in the kit)

Only for 3 Door Application

409.36.050

For Door Thickness of 28 mm

External Central Double Side Soft Close door kit consists of:

- > 2 Steel Adjustable Upper Slide
- > 2 Steel Lower Slide with Wheel and O-Ring
- > 1 Right Plastic Adjustable Upper Lock
- > 1 Left Plastic Adjustable Upper Lock
- > 1 Plastic Upper Central Lock.
- > 2 Plastic Lower Lock
- > 1 Rounded Socket Key with 4 mm Hexagonal Ends
- > 1 Central Double Side Soft Close
- > 1 Soft Close

409.36.051

For Door Thickness of 38 mm

External Central Double Side Soft Close door kit consists of:

- > 2 Steel Adjustable Upper Slide
- > 2 Steel Lower Slide with Wheel and O-Ring
- > 1 Right Plastic Adjustable Upper Lock
- > 1 Left Plastic Adjustable Upper Lock
- > 1 Plastic Upper Central Lock.
- > 2 Plastic Lower Lock
- > 1 Rounded Socket Key with 4 mm Hexagonal Ends
- > 1 Central Double Side Soft Close
- > 1 Soft Close


Classic IF 45




Straight sliding system for wooden wardrobe and furniture doors.

Hardware Specification:

- > Vertical adjustment mechanism which enable adjustment up to 6 mm
- > For doors with thickness of 16 and 19 mm
- > Rolling system with ball bearing wheels
- > For single or double guide applications

Product Name	Article No.	
Silver anodized aluminium top single track (Note: Track to be ordered separately)	405.21.603	3000 mm
Silver anodized aluminium top double track (Note: Track to be ordered separately)	405.21.613	3000 mm
Brake stop (Note: Brake stop to be ordered separately)	405.21.300	-


- 405.21.100
Sliding door kit consists of:
- > 2 Rollers with Bracket
 - > 1 Bottom Guide

Classic 80 W


Straight sliding system for wooden doors.

Hardware Specification:

- > Ideal for dividers and internal doors
- > An elegantly designed top quality system
- > Concealed lower guide
- > Roller comes with an elastic system for absorbing the irregularities of profile (If any)
- > High quality Zamak aluminium body
- > Proven smooth and silent rolling, thanks to our special anti dust ball bearing system
- > Rollers for long lasting rolling durability

Product Name	Article No.	
Aluminium anodized top track (Note: Track to be ordered separately)	409.50.602	2100 mm
Aluminium anodized top track (Note: Track to be ordered separately)	941.27.432	3000 mm

409.79.020

Sliding door kit consists of:

- > 2 Rollers with Bracket
- > 1 Bottom Guide
- > 2 Adjustable Stoppers and other fittings

Classic 120 S




Straight synchro sliding system for wooden doors.


Hardware Specification:

- > Synchro system for simultaneous opening of both the doors
- > Solid rollers made of high quality Zamak one piece die casting
- > High tech hanger made of high quality Zamak alloy with solid structure and discrete design

941.10.035

- > Sliding door kit consists of:
- > 4 Rollers with Bracket
- > 2 Bottom Guides
- > 2 Pulley Door Profiles
- > 2 Cable Brackets
- > 8 m Steel Cable
- > 2 Stoppers and other fittings

Product Name	Article No.	
Aluminium anodized top track (Note: Track to be ordered separately)	941.10.915	1524 mm
	941.10.918	1828 mm
	941.10.921	2134 mm
	941.10.924	2438 mm
	941.10.927	2743 mm
	941.10.930	3048 mm
	941.10.936	3657 mm

Design 100 C


Straight sliding system for glass doors.

Hardware Specification:

- > System with robust and elegant hangers
- > Stopper with inbuilt spring action to prevent vibration
- > Roller hanger having offset shaft for adjusting door panel up and down
- > Plastic roller wheels having higher anti wear performance

Product Name	Article No.	L mm
Aluminium anodized running track (Note: Track to be ordered separately)	941.16.915	1500 mm
	941.16.918	1800 mm
	941.16.921	2100 mm
	941.16.924	2400 mm
	941.16.927	2700 mm
	941.16.930	3000 mm


Product Name	Article No.	Finish
2 Rollers	941.16.012	SS matt
End Door Stopper	941.16.042	SS matt
Middle Door Stopper	941.16.043	SS matt
Glass Support for Track	941.16.031	SS matt
Wall Support for Track	941.16.032	SS matt
End Wall Support for Track	941.16.033	SS matt
Universal Joint for Track	941.16.034	SS matt
Bottom Guide for 10 or 12mm Glass	941.16.035	SS matt
Fixing Tool	941.16.036	SS matt

Häfele Ironfix Ironing board



Installation behind drawer front panels,
aluminium coated ironing board cover

568.60.723




Stored with direct access
in a space saving way

- > Version: Collapsible,
ironing board supports automatically
extend when the drawer is opened,
continuous width adjustment
- > Internal inner width !: 362–500 mm
- > Internal cabinet depth ": <500 mm



Installation on shelf,
aluminium coated ironing board cover

568.60.793



Stored with direct access in a space
saving way


- > Version: Folding,
rotating 180° with positioning
at 15° intervals, fully pre-mounted
without front connection
- > Installation depth: 350 mm
- > Installation height: 125 mm
- > Installation width: 540 mm

Häfele Ironfix Ironing board



Wall mounted,
aluminium coated ironing board cover

568.66.723



Stored with direct access
in a space saving way

- > Version: Folding,
180° continuously rotating and
locking, fully pre-mounted


Covering hood, for Häfele Ironfix wall mounted ironing board



Plastic, white


568.66.790

Ironing board, incl. supports for ironing board and iron



Ironing board incl. support

983.25.089



- > Version: Collapsible ironing board
(silver coloured cover)
incl. holder, an iron can also be placed in the holder
(iron not included in scope of delivery)
- > Dimensions: Ironing board area 1220 x 340 mm
- > Installation: For screw fixing, e.g. in a cabinet

Häfele Duoletto Built-in foldaway bed



- > Area of application: Usable as individual bed or bunk bed (2 fitting sets)
- > Version: Foldaway bed with frame and slatted frame, including anti-tilt facility and retaining straps / brackets for bedding and mattress
- > Weight of bed: 55–85 kg, gas-filled struts make it possible to conveniently fold the bed in and out
- > For mattress size: 900 x 2000 mm
- > Load bearing capacity: 100 kg
- > Installation: Variable and freely selectable installation height when used as single bed

Built-in foldaway bed

Without mattress

271.89.000

With mattress

271.89.005

Häfele Teleletto II Foldaway bed fitting for sofa bed



Quick change from sofa to bed;
extra large lying area

- > Area of application: Built-in foldaway bed and sofa
- > Version: Built-in foldaway bed with bed frame, slatted frame, sofa frame and angular feet, including anti-tilt facility and retaining straps / brackets for bedding and mattress
- > Weight of bed: 74-110 kg, gas-filled struts make it possible to conveniently fold the bed in and out
- > For mattress size: 1400 x 2000 mm
- > Sofa dimensions: 2057 x 700 mm
- > Load bearing capacity: 100 kg
- > Installation: Variable and freely selectable installation height when used as single bed
- > 7 zone mattress version: Cover removable and washable at 60°, suitable for allergy sufferers,
- > 1400 x 2000 mm, lying comfort provided by dimensional stability, high point stability,
- > Provides optimum spinal support and good ventilation, open pored foam structure with moisture transport, firmness rating H3 – body weight up to 90 kg

Häfele Teleletto II

Foldaway bed fitting for sofa bed
without mattress

271.89.020

Replacement gas-filled strut for Teleletto II
foldaway bed fitting for sofa bed

271.99.186

7-zone mattress with cold foam core

271.67.204

Kettle



- Volume: 1.7 L
- Power: 2150 W
- Food Grade Stainless Steel inner & outer body
- Analog temperature display
- UK Strix Control for precise heating
- Indicator light on switch
- Detachable Micro-mesh Filter
- External water gauge
- Automatic & manual switch off
- Boil-dry protection
- Colors: Opal (Metallic red) & Jade (Matt grey)

DOME KETTLE

535.43.542 (Jade)
535.43.540 (Opal)

Kettle



- > Volume: 1.6 L
- > Power: 2150 W
- > Double lining of Stainless Steel and Plastic
- > Analog temperature display
- > UK Strix Control for precise heating
- > Indicator light on switch
- > Detachable Micro-mesh Filter
- > External water gauge
- > Automatic & manual switch off
- > Boil-dry protection
- > Color: Royal white with rose gold highlights

QUEEN KETTLE

535.43.541

Pedal BINS



- > Soft closure and super-light pedal operation
- > Odour-proof closure
- > Easy to clean with a removable inner bucket
- > Non-slip base protects the floor and keeps the bin steady
- > Cradle to cradle certified
- > Made up of 40% high-grade recycled materials and after use, 98% of the bin and packaging is recyclable
- > Colour Options: Stainless Steel (Anti-Fingerprint), Platinum, Passion Red and White
- > Material: Pre-coated Stainless Steel Grade 304



- > Stainless Steel Anti Fingerprint
- > W205*XD272*XH291 (5L)
- > Article No: 503.83.171
- > W251*XD338*XH411 (12L)
- > **503.83.173**



- > Passion Red
- > W205*XD272*XH291 (5L)
- > Article No: 503.83.971
- > W251*XD338*XH411 (12L)
- > **503.83.973**



- > Platinum
- > W205*XD272*XH291 (5L)
- > Article No: 503.83.071
- > W251*XD338*XH411 (12L)
- > **503.83.073**



- > White
- > W205*XD272*XH291 (5L)
- > Article No: 503.83.771
- > W251*XD338*XH411 (12L)
- > **503.83.773**

Wall mounted TV support bracket



Steel, powder coated black

817.35.301

- > Area of application:
For monitors with diagonal of 10" to 32"
- > Adjustment facility:
Tilting: +15° to -5°; swivelling: ±15°
- > VESA standard:
100 x 100 mm, 200 x 100 mm, 200 x 200 mm
- > Load bearing capacity: 27 kg
- > Installation: For screw fixing



Steel, powder coated black

817.35.322

- > Area of application:
For monitors with diagonal of 32" to 55"
- > Adjustment facility: Tilting: +12° to -12°
- > VESA standard: 600 x 400 mm
- > Load bearing capacity: 79 kg
- > Installation: For screw fixing




Lighting Solutions

PAGE

93

Lighting Solutions – Product overview

LOOX LED 2034/2035, 12 V




LOOX LED 2027 SURFACE MOUNTED DOWNLIGHT



LOOX LED 2019 GLASS EDGE LIGHT



LOOX LED 2020 RECESS MOUNTED LIGHT/SUR- FACE MOUNTED DOWNLIGHT




RECESS / SURFACE MOUNTED DOWNLIGHT




RECESS / SURFACE MOUNTED DOWNLIGHT




LED STRIP LIGHT, Monochrome, 5 m,




LED STRIP LIGHT, Monochrome, 8 m,




LED STRIP LIGHT, Multi White, 8 m,




LED STRIP LIGHT, RGB ,12m,



LED DRAWER LIGHT



LOOX ALUMINIUM PROFILES FOR LED LIGHT



DIFFUSER



HÄFELE CONNECT BLE BOX



SWITCHES



MECHANICAL SWITCHES



Lighting Solutions – Product overview

LEADS AND DISTRIBUTORS




LOOX LED DRIVER




CHARGING STATION



AQUASYS LIGHT MIRROR




420E SOUND SYSTEM




POP UP SOCKET



Häfele Loox LED 2034 Flexible light, 12 V - Monochrome with USB



- > Dimmable: Yes
- > Version: Integrated twin USB charging station 5 V / 2 A, integrated push switch for 2 brightness levels
- > Material: Aluminium
- > Length x width: 450 x 50 mm
- > Height: 15.5 mm
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Number of LEDs: 3
- > Mounting: For screw fixing beneath magnetic cover
- > Supplied with: 1 light with 2 m lead including fixing materials


12 V

Loox 12 V driver see page 134

Min. 20 W driver per light for optimum operation of the USB charging station.

Voltage	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI	Weighted energy consumption kWh/1000 h	Finish/colour	Cat. No.
	K	W	lm	lm/W	R _a			
12 V	4000	17 (light: 1.5)	105	70	82	1.65	Black	833.74.097

Häfele Loox LED 2035 Flexible light, 12 V - Monochrome



- > Dimmable: Yes
- > Version: Integrated push switch for 2 brightness levels
- > Material: Aluminium
- > Length x width: 450 x 50 mm
- > Height: 15.5 mm
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Number of LEDs: 3
- > Mounting: For screw fixing beneath magnetic cover
- > Supplied with: 1 light with 2 m lead, including fixing materials


12 V

Loox 12 V driver see page 134

Voltage	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI	Weighted energy consumption kWh/1000 h	Finish/colour	Cat. No.
	K	W	lm	lm/W	R _a			
12 V	4000	1.5	105	70	82	1.65	Black	833.74.153



LOOX LED 2027 SURFACE MOUNTED DOWNLIGHT, ROUND

12 V SYSTEM




The flat LED 2027 surface mounted downlight can be used universally. The edge is illuminated, and the points of the LED light are not visible. The fixings are concealed beneath a removable cover.



Dimmable
Installation: For screw fixing

Article No.:	833.72.050	833.72.051	833.72.052
Colour temperature (K)	3000 (warm white)	4000 (natural white)	5000 (cool white)
Ø (mm)	65	65	65
Height (mm)	9	9	9
Wattage (W)	2.6	2.6	2.6
Number of LEDs	27	27	27
Luminous flux (lm)	190	208	218
Lum. efficacy (lm/W)	73	80	84
Colour rendering index (CRI)	85	85	85
Energy efficiency class	A+	A+	A+
Weighted energy consumption (kWh/1.000 h)	2.86	2.86	2.86
Finish	Aluminium, silver coloured, plastic		
Supplied with	1 light with 2 m lead and fixing material		



3000 K	4000 K	5000 K	
867 lx	884 lx	918 lx	250 mm
216 lx	221 lx	229 lx	500 mm
96 lx	98 lx	102 lx	750 mm
54 lx	55 lx	57 lx	1000 mm

LOOX LED 2019 GLASS EDGE LIGHT WITH VISIBLE LIGHT POINTS




12 V SYSTEM



The LED 2019 opens up a wide range of possible uses. Glass panels between 6 and 12 mm thick can be used with this light.



Dimmable
Without load bearing function
Is pushed onto the glass shelf
from the rear
Glass thickness 6–12 mm



Article No.:	833.74.130	833.74.120
Colour temperature (K)	4000 (natural white)	6000 (cool white)
Length (mm)	40	40
Width (mm)	25.5	25.5
Height (mm)	12	12
Wattage (W)	0.2	0.2
Number of LEDs	3	3
Luminous flux (lm)	15	19
Lum. efficacy (lm/W)	75	95
Colour rendering index (CRI)	88	84
Material	Stainless steel	
Finish/colour	Bright	
Supplied with	1 light with 2 m lead	


LOOX LED 2020 RECESS MOUNTED LIGHT/SURFACE MOUNTED DOWNLIGHT, ROUND

12 V SYSTEM




The LED 2020 generates homogeneous, extensive light and is ideal for atmospheric lighting in any area – and with the IP44 degree of protection the recess mounted light can also be used in wet rooms.

The light can be used in a variety of ways because of the two installation types and three colour temperatures.



Article No.:	833.72.280	833.72.281	833.72.282	833.72.283	833.72.284	833.72.285	833.72.286	833.72.287	833.72.288
Colour temperature (K)	3000 (warm white)			4000 (natural white)			5000 (cool white)		
Ø (mm)	65	65	65	65	65	65	65	65	65
Height (mm)	14.7	14.7	14.7	14.7	14.7	14.7	14.7	14.7	14.7
Degree of protection	IP44 as recess mounted light; IP20 with downlight housing (surface mounted downlight)								
Wattage (W)	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2	3.2
Number of LEDs	6	6	6	6	6	6	6	6	6
Luminous flux (lm)	142	142	142	150	150	150	150	150	150
Lum. efficacy (lm/W)	44	44	44	47	47	47	47	47	47
Colour rendering index (CRI)	83	83	83	83	83	83	83	83	83
Energy efficiency class	A	A	A	A	A	A	A	A	A
Weighted energy consumption (kWh/1.000 h)	3.52	3.52	3.52	3.52	3.52	3.52	3.52	3.52	3.52
Material	Zinc alloy			Zinc alloy			Zinc alloy		
Finish/colour	Matt nickel plated	Black	Polished-Chrome Plated	Matt nickel plated	Black	Polished-Chrome Plated	Matt nickel plated	Black	Polished-Chrome Plated
Supplied with	1 light with 2 m lead and fixing material								

LOOX LED 2020 RECESS MOUNTED LIGHT/SURFACE MOUNTED DOWNLIGHT, ROUND


Dimmable
Drill hole Ø: 55 mm



Downlight housing
Black: **833.72.801**
Matt nickel plated: **833.72.800**
Polished chrome plated: **833.72.802**

With a downlight housing the degree of protection is IP20.

Recess/surface mounted downlights - Multi-white, drill hole Ø: 55 mm



Häfele Loox LED 2048/3039

12 V/ 24V
SYSTEM



! Use Häfele BLE Box to operate Multi white LED Lights.
See page 88

12 V Loox 12 V driver see page 134

24 V Loox 24 V driver see page 134

- > Dimmable: Yes, via Häfele BLE box
- > Material: Steel
- > Finish: Silver coloured, Polished chrome plated
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Mounting: For mounting in drilled hole, for clamp fixing or for screw fixing
- > Drill hole Ø: 55 mm
- > Supplied with: 1 light with 2 m multi-white lead

LED 2048

2700 K	5000 K	120°	
290 lx	345 lx		250 mm
110 lx	130 lx		500 mm
60 lx	70 lx		750 mm
40 lx	45 lx		1000 mm

LED 3039

2700 K	5000 K	120°	
335 lx	350 lx		250 mm
125 lx	130 lx		500 mm
70 lx	70 lx		750 mm
45 lx	45 lx		1000 mm

Häfele Loox LED 2048 / 3039

Voltage V	Number of LEDs	Colour temperature K	Wattage W	Luminous flux lm	Luminous efficacy lm/W	Colour rendering index CRI R _a	Weighted energy consumption kWh/1000 h	Silver coloured	Polished chrome plated
12 V	Häfele Loox LED 2048								
	60	2700 - 5000	3	255	85	90 83	3.3	833.72.311	833.72.310
24 V	Häfele Loox LED 3039								
	60	2700 - 5000	3	258	85	90 83	3.3	833.75.131	833.75.130



Downlight housing

Colour	Cat. No.
Silver coloured	833.72.803
Polished chrome plated	833.72.802

Recess/surface mounted downlights - Modular, drill hole Ø: 58 mm


Häfele Loox LED 2026



- > Dimmable: Yes
- > Material: Aluminium
- > Finish: Polished chrome plated
- > Energy efficiency class: A+
- > Degree of protection: IP44 as recess mounted downlight;
IP20 as surface mounted downlight
- > Mounting: For mounting in drilled hole, for clamp fixing or for screw fixing
- > No. of LED: 6
- > Drill hole Ø: 58 mm
- > Supplied with: 1 light module

Voltage	Quantity	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index	Weighted energy consumption	Cat. No.
V	LEDs	K	W	lm	lm/W	R _a	R ₉	kWh/1000 h
5 12 V	Häfele Loox LED 2026							
12 V	1	2700	3.0	185	62	>90	—	3.30
		3000	3.0	210	70	>90	—	3.30
		4000	3.0	221	74	>90	—	3.30
		5000	3.0	260	87	>83	—	3.30

LED 2026					80°
2700 K	3000 K	4000 K	5000 K		
1400 lx	1800 lx	1850 lx	1950 lx	250 mm	
400 lx	500 lx	520 lx	550 lx	500 mm	
175 lx	225 lx	235 lx	250 lx	750 mm	
100 lx	125 lx	135 lx	140 lx	1000 mm	




Lead, 1.5 A/24 AWG, with snap-in connector

Voltage	Length	Cat. No.
12 V	500 mm	833.72.880
	1000 mm	833.72.881
	2000 mm	833.72.882



Recess mounted housing




Downlight housing



Housing for recess mounting, plastic

Colour	Round	Square
Silver coloured	833.72.126	833.72.127
Black	833.72.168	833.72.172
Stainless steel coloured	833.72.382	833.72.385



Downlight housing, plastic

Colour	Round	Square
Silver coloured	833.72.124	833.72.125
Black	833.72.160	833.72.164
Stainless steel coloured	833.72.194	833.72.197



Note

The IP44 degree of protection is reduced to IP20 when mounting as downlight or recess mounting with through hole.



LOOX LED STRIP LIGHT, Monochrome, 5 mm



Häfele Loox5 LED 2061; High Performance



LED 2061

Equipped with high-quality Samsung LEDs

- > Dimmable: Yes
- > Material: Plastic
- > Finish/colour: White
- > Width: 5 mm
- > Height: 1.3 mm
- > Life time L80/B10: >50,000 h
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Mounting: Self-adhesive
- > Supplied with: 1 roll

Voltage	Quantity	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI		Weight. energy consumpt. per m in kWh/1000 h	Section length C	Length of contact surface P	Max. strip length (visual)	Available length
V	LEDs/m	K	W/m	lm/m	lm/W	R _a	R ₉		mm	mm	m	5 m
Häfele Loox5 LED 2061												
5 12V	120	2700	9.6	870	91	>90	>50	10.56	25	3	3.0	833.74.328
		3000	9.6	830	97	>90	>50	10.56	25	3	3.0	833.74.329
		4000	9.6	955	99	>90	>50	10.56	25	3	3.0	833.74.330
		5000	9.6	990	103	>90	>50	10.56	25	3	3.0	833.74.331



Maximum visual strip length applies for an imperceptible drop in luminous flux of max. 30%.




> 3.5 A/20 AWG lead for LED strip light 5 mm

Voltage	Length mm	Cat. No.
5 12V	2000	833.72.742



> 3.5 A clip connector for 5 mm LED strip light

	Cat. No.
Clip connector	833.89.207



> 3.5 A/20 AWG interconnecting lead for 5 mm LED strip light

Length mm	Cat. No.
500	833.89.195



> Corner connector, 90° rigid, 3.5 A for left or right for 5 mm LED strip light

	Cat. No.
Corner connector rigid	833.89.190

LOOX LED STRIP LIGHT, Monochrome, 8 mm

Häfele Loox5 LED 2062 / 2068 / 3048; High Performance



LED 2062



LED 2068



LED 3048

- > Dimmable: Yes
- > Material: Plastic
- > Finish/colour: White
- > Width: 8 mm
- > Height: 1.3 mm
- > Life time L80/B10: >50,000 h
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Mounting: Self-adhesive
- > Supplied with: 1 roll

Equipped with high-quality Samsung LEDs




Order reference:
Please order lead separately.

Voltage	Quantity	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI		Weight. energy consumpt. per m in kWh/ 1000 h	Section length C	Length of contact surface P	Max. strip length (visual)	Available length	
V	LEDs/m	K	W/m	lm/m	lm/W	R _a	R _g		mm	mm	m	5 m	
<div>5 12V</div>	Häfele Loox5 LED 2062												
	60	2700	4.8	440	92	>90	>50	5.28	50	4	6.0	833.74.336	
		3000	4.8	465	97	>90	>50	5.28	50	4	6.0	833.74.337	
		4000	4.8	490	102	>90	>50	5.28	50	4	6.0	833.74.338	
		5000	4.8	495	103	>90	>50	5.28	50	4	6.0	833.74.339	
	Häfele Loox5 LED 2068												
	120	2700	9.6	920	96	>90	>50	10.56	25	4	4.0	833.74.362	
		3000	9.6	970	101	>90	>50	10.56	25	4	4.0	833.74.363	
		4000	9.6	1000	104	>90	>50	10.56	25	4	4.0	833.74.364	
		5000	9.6	1040	108	>90	>50	10.56	25	4	4.0	833.74.365	
	Häfele Loox5 LED 3048												
	<div>5 24V</div>	120	2700	14.4	1270	88	>90	>50	15.84	50	4	6.2	833.76.352
			3000	14.4	1305	91	>90	>50	15.84	50	4	6.2	833.76.353
			4000	14.4	1340	93	>90	>50	15.84	50	4	6.2	833.76.354
			5000	14.4	1430	99	>90	>50	15.84	50	4	6.2	833.76.355



Maximum visual strip length applies for an imperceptible drop in luminous flux of max. 30%.




> 5 A/18 AWG lead for LED strip light 8 mm

Voltage	Length mm	Cat. No.
5 12 V	2000	833.72.716
5 24 V	2000	833.75.705



> 5 A clip connector for 8 mm LED strip light

	Cat. No.
Clip connector	833.89.206



> 5 A/18 AWG interconnecting lead for 8 mm LED strip light

Length mm	Cat. No.
500	833.89.192



> Corner connector, 90° rigid, 5 A for left or right for 8 mm LED strip light

	Cat. No.
Corner connector rigid	833.89.187



5 YEARS
GUARANTEE



IP20



LOOX LED STRIP LIGHT, Monochrome, 8 mm

Häfele Loox5 LED 3052; High Performance



LED 3052

Constant current technology

- > Achieves uniform brightness over the entire strip light length
- > Increased life time, higher visual strip length, higher luminous efficacy

Equipped with high-quality Samsung LEDs




- > Dimmable: Yes
- > Material: Plastic
- > Finish/colour: White
- > Width: 8 mm
- > Height: 1.5 mm
- > Life time L80/B10: >70,000 h
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Mounting: Self-adhesive
- > Supplied with: 1 roll

Voltage	Quantity	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI		Weight. energy consumpt. per m in	Section length C	Length of contact surface P	Max. strip length (visual)	Available length
V	LEDs/m	K	W/m	lm/m	lm/W	R _a	R ₉	kWh/1000 h	mm	mm	m	5 m
Häfele Loox5 LED 3052												
5^{24V}	140	2700	19.2	1850	96	>90	>50	21.12	50	3	4.6	833.76.378
		3000	19.2	2015	105	>90	>50	21.12	50	3	4.6	833.76.379
		4000	19.2	2050	107	>90	>50	21.12	50	3	4.6	833.76.380
		5000	19.2	2100	109	>90	>50	21.12	50	3	4.6	833.76.381



The maximum visual strip length for Loox 5 constant current strips is the length without drop in luminous flux.




> 5 A/18 AWG lead for LED strip light 8 mm

Voltage	Length mm	Cat. No.
5^{24V}	2000	833.75.705



> 5 A clip connector for 8 mm LED strip light

	Cat. No.
Clip connector	833.89.206



> 5 A/18 AWG interconnecting lead for 8 mm LED strip light

Length mm	Cat. No.
500	833.89.192



> Corner connector, 90° rigid, 5 A for left or right for 8 mm LED strip light

	Cat. No.
Corner connector rigid	833.89.187

LOOX LED STRIP LIGHT, Multi-white, 8 mm

Häfele Loox5 LED 2071 / 2074; Standard



LED 2071



LED 2074

- > Dimmable: Yes
- > Material: Plastic
- > Finish/colour: White
- > Width: 8 mm
- > Height: 1.3 mm
- > Life time L80/B10: >30,000 h
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Mounting: Self-adhesive
- > Supplied with: 1 roll



Equipped with high-quality Samsung LEDs




Order reference:
Please order lead separately.

Voltage	Quantity	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI		Weight. energy consumpt. per m in kWh/1000 h	Section length C	Length of contact surface P	Max. strip length (visual)	Available length
V	LEDs/m	K	W/m	lm/m	lm/W	R _a	R ₉		mm	mm	m	5 m
5 12 V	Häfele Loox5 LED 2071											
	60	2700	4.8	440	92	90	>50	5.28	50	4	6.0	833.74.300
		3000	4.8	465	97	90	>50	5.28	50	4	6.0	833.74.301
		4000	4.8	490	102	90	>50	5.28	50	4	6.0	833.74.302
		5000	4.8	495	103	90	>50	5.28	50	4	6.0	833.74.303
	Häfele Loox5 LED 2074											
	120	2700	9.6	920	96	90	>50	10.56	25	4	3.5	833.74.308
		3000	9.6	970	101	90	>50	10.56	25	4	3.5	833.74.309
		4000	9.6	1000	104	90	>50	10.56	25	4	3.5	833.74.310
		5000	9.6	1040	108	90	>50	10.56	25	4	3.5	833.74.311



Maximum visual strip length applies for an imperceptible drop in luminous flux of max. 30%.




> 5 A/18 AWG lead for LED strip light 8 mm

Voltage	Length mm	Cat. No.
5 12 V	2000	833.72.716



> 5 A clip connector for 8 mm LED strip light

	Cat. No.
Clip connector	833.89.206



> 5 A/18 AWG interconnecting lead for 8 mm LED strip light

Length mm	Cat. No.
500	833.89.192



> Corner connector, 90° rigid, 5 A for left or right for 8 mm LED strip light

	Cat. No.
Corner connector rigid	833.89.187

LOOX LED STRIP LIGHT, Multi-white, 8 mm

Häfele Loox5 LED 2073 / 2076; Standard



LED 2073



LED 2076

- > Dimmable: Yes
- > Material: Plastic
- > Finish/colour: White
- > Width: 8 mm
- > Height: 1.3 mm
- > Life time L80/B10: >30,000 h
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Mounting: Self-adhesive
- > Supplied with: 1 roll


Optimised light mixture

- > Cool white and warm white LEDs in the smallest of spaces
- > Optimal light mixture without flickering

! Order reference:
Please order lead separately.

Voltage	Quantity	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI		Weight. energy consumpt. per m in	Section length C	Length of contact surface P	Max. strip length (visual)	Available length
V	LEDs/m	K	W/m	lm/m	lm/W	R _a	R ₉	kWh/1000 h	mm	mm	m	5 m
5 12V	Häfele Loox5 LED 2073											
	2 x 60	2700 5000	4.8	425 465	88 96	90	>50	5.28	50	4	4.5	833.74.316
	Häfele Loox5 LED 2076											
	2 x 120	2700 5000	9.6	875 940	91 97	90	>50	10.56	25	3.5	3	833.74.318

! Maximum visual strip length applies for an imperceptible drop in luminous flux of max. 30%.



> 3.5 A/20 AWG lead for 8 mm multi-white LED strip light

Length mm	Cat. No.
500	833.72.717



> 3.5 A clip connector for 8 mm multi-white LED strip light

Clip connector	Cat. No.
Clip connector	833.89.208



> Corner connector 90° rigid, 3.5 A for left or right for 8 mm multi-white LED strip light

Corner connector rigid	Cat. No.
Corner connector rigid	833.89.188



> 3.5 A/20 AWG interconnecting lead for 8 mm multi-white LED strip light

Length mm	Cat. No.
500	833.89.198

+ Use Häfele BLE Box to operate the multi-white strip lights. See page 125

LOOX LED STRIP LIGHT, RGB, 12 mm

Häfele Loox LED 2016



LED 2016



- > Dimmable: Yes, via Häfele connect BLE app
- > Material: Plastic
- > Finish/colour: LED board, white
- > Length: 5000 mm
- > Width: 12 mm
- > Height: 2.4 mm
- > Life time L70/B50: 30,000 h
- > Energy efficiency class: A+
- > Degree of protection: IP20
- > Installation: Self-adhesive
- > Supplied with: 5 m roll and 2 m lead 2.5 A/22 AWG






Bright light sources with changing colours are often in demand for lighting. The LED 2016 colour changing strip light meets these requirements easily.



Order reference:
Please order lead separately.

Voltage	Quantity	Colour temperature	Wattage	Luminous flux	Luminous efficacy	Colour rendering index CRI		Weight. energy consumpt. per m in	Section length C	Length of contact surface P	Max. strip length (visual)	Available length
V	LEDs/m	K	W/m	lm/m	lm/W	R _a	R ₉	kWh/1000 h	mm	mm	m	5 m
12V	Häfele Loox5 LED 2016											
	30	RGB	7.1	1050	29	-	-	-	100	-	3.4	833.73.450

Häfele Loox LED 2016

	> Lead, 2.5 A/22 AWG, with clip for LED RGB strip light			> Corner connector, rigid, 2.5 A, for LED RGB strip light	
	Voltage	Length mm	Cat. No.		Cat. No.
	12V	2000 mm	833.74.764	Corner connector	833.74.760
		4000 mm	833.74.745		
	> Interconnecting lead, 2.5 A/22 AWG, with clip for LED RGB strip light			> Clip connector, 2.5 A for LED RGB strip light	
					Cat. No.
	50 mm			Clip connector	833.74.761
	500 mm				
	1000 mm				
	2000 mm				



Maximum visual strip length applies for an imperceptible drop in luminous flux of max. 30%.



Use Häfele BLE Box to operate Multi white LED Lights. See page 125

LED DRAWER light with infra red sensor


12 V SYSTEM



LED Drawer Light helps you locate and search through the drawer and cabinet contents. The inbuilt sensor gets activated by the movement of door, automatically switching on and off as you open and close the drawer / shutter.


The LED Drawer Light provides you flexibility to install in two different ways: Side Installation for drawers (in case there is space restriction) and top installation for both drawers and cabinets.

- > LED Drawer Light with Built-in Infra Red Sensor
- > Life: 50,000 hours



Article No.:	833.01.003	833.01.006
Colour temperature (K)	6400 (cool white)	
L X W X H (mm)	563 X 18 X 14	863 X 18 X 14
Finish	Silver Anodized Aluminum Profile	
Output	2.4W	5.2W

Article No.:	833.71.836	833.71.889
Colour temperature (K)	5000 (cool white)	
L X W X H (mm)	863 X 18 X 13	562 X 18 X 13
Finish	Silver Anodized Aluminum Profile	
Output	6W	






Profiles for recess mounting - Aluminium


Häfele Loox5 profile 1104/1103



Häfele Loox5 profile 1104



End caps





- > Material: Profile: Aluminium, Diffuser: Plastic
- > Finish/colour: Profile: Anodized, Diffuser: White opal, transmittance 70–80 %
- > Length: 3000 mm
- > Diffuser width: Profile 1104: 8 mm, Profile 1103: 11 mm
- > Supplied with: 1 aluminium profile
1 diffuser white opal


Colour	Profile 1104	Profile 1103
Black	833.95.725	833.95.723
Silver coloured	833.95.724	833.95.722

Note
Profile 1104 is usable for LED strip lights up to max. 5 mm width.

Häfele Loox5 profile 1103



End caps



+ End caps for Häfele Loox5 profile 1104, 1103

- > Material: Plastic
- > Version: With cable outlet
- > Supplied with: 5 pairs of end caps

Colour	End cap 1104	End cap 1103
Black	833.95.769	833.95.767
Silver coloured	833.95.768	833.95.766

Diffusers
The diffuser creates a uniform light.
The LED points are invisible from 120 LEDs/m.
If required, please order alternative diffuser in black opal separately.


➔ Diffusers see page 123

Profiles for recess mounting - Aluminium

Häfele Loox5 profile 1105, asymmetric light distribution



Häfele Loox5 profile 1105



Anti-glare shield

Asymmetric light distribution allows for a glare-free light source.

- > Material: Profile: Aluminium, Diffuser: Plastic
- > Finish/colour: Profile: Anodized, Diffuser: White opal, transmittance 70–80 %
- > Length: 3000 mm
- > Diffuser width: 11 mm
- > Supplied with: 1 aluminium profile
1 diffuser white opal

Colour	Cat. No.
Black	833.95.727
Silver coloured	833.95.726

+ End caps for Häfele Loox5 profile 1105

- > Material: Plastic
- > Version: With cable outlet
- > Packing:: 10 pieces


Colour	Cat. No.
Black	833.95.771
Silver coloured	833.95.770

- ! **Diffusers**
The diffuser creates a uniform light.
The LED points are invisible from 120 LEDs/m.
If required, please order alternative diffusers in black or transparent separately.


➔ Diffusers see page 123

Profiles for recess mounting - Aluminium

Häfele Loox profile for recess mounting



End cap



- > Material: Aluminium
- > Finish/colour: Silver coloured anodized
- > Length x width: 2500 x 18 mm
- > Height: 8.5 mm
- > Supplied with: 1 profile, 1 diffuser

Colour	Cat. No.
Silver coloured with milky diffuser	833.72.844



LED points are always visible when this profile is used



End cap with cable outlet for 833.72.844


- > Material: Plastic
- > Supplied with: 2 pieces

Colour	Cat. No.
Silver coloured	833.72.855




Diffusers see page 123

Häfele Loox profile for recess mounting



End cap



- > Material: Aluminium
- > Finish/colour: Silver coloured anodized
- > Length x width: 2500 x 18 mm
- > Height: 13 mm
- > Supplied with: 1 profile, 1 diffuser

Colour	Cat. No.
Silver coloured with milky diffuser	833.72.846



End cap with cable outlet for 833.72.846

- > Material: Plastic, silver coloured
- > Supplied with: 2 pieces

Colour	Cat. No.
Silver coloured	833.72.854



Diffusers see page 123




Profiles for recess mounting - Aluminium

Häfele Loox5 profile 1107 / 1106



Häfele Loox5 profile 1107,
with asymmetric light distribution




- > Material: Profile: Aluminium, Diffuser: Plastic
- > Finish/colour: Profile: Anodized, Diffuser: White opal, transmittance 70–80 %
- > Length: 3000 mm
- > Diffuser width: Profile 1107: 8 mm, Profile 1106: 11 mm
- > Supplied with: 1 aluminium profile
1 diffuser white opal

Colour	Profile 1107	Profile 1106
Black	833.95.731	833.95.729
Silver coloured	833.95.730	833.95.728

! Profile 1107 is usable for LED strip lights up to max. 5 mm width. Glare-free light, ideal for vertical installation in wardrobes.

Häfele Loox5 profile 1106,
with asymmetric light distribution



End caps

+ End caps for Häfele Loox5 profile 1106

- > Material: Plastic
- > Version: With cable outlet
- > Mounting: For screw fixing
- > Supplied with: 5 pairs of end caps with screws

Colour	Article No.
Black	833.95.773
Silver coloured	833.95.772

! **Diffusers**
The diffuser creates a uniform light.
If required, please order alternative diffuser in black opal separately.


➔ Diffusers see page 123

Profiles for recess mounting - Poly-carbonate

Häfele Loox5 profile 1102 / 1101




Häfele Loox5 profile 1102



- > Material: Poly-carbonate
- > Finish/colour: White & Black Opal
- > Length: 3000 mm
- > Supplied with: 1 Poly-carbonate profile

Colour	Transmittance	Profile 1102	Profile 1101
Black	~20 %	833.95.741	833.72.899
White	70-80 %	833.95.740	833.72.898

Häfele Loox5 profile 1101

**Note**

Profiles 1102 and 1101 are usable for LED strip lights up to max. 9.6 W/m.


Profile 1102 is usable for LED strip lights up to max. 5 mm width. Profile 1101 is usable only for LED strip lights with a width of precisely 8 mm.

The diffuser creates a uniform light.

The LED points in the white version are invisible from 120 LEDs/m.

Profiles for recess mounting - Aluminium

Häfele Loox5 profile 2102



End caps

Flush recess mounted diffuser

- > Material: Profile: Aluminium, Diffuser: Plastic
- > Finish/colour: Profile: Anodized, Diffuser: White opal, transmittance 70–80 %
- > Length: 3000 mm
- > Diffuser width: 11 mm
- > Supplied with: 1 aluminium profile
1 diffuser white opal

Colour	Profile 2102
Black	833.95.735
Brushed stainless steel coloured	833.95.763



Diffusers
The diffuser creates a uniform light. The LED points are invisible from 120 LEDs/m. If required, please order alternative diffuser in black opal separately.



Diffusers see page 123



End caps for Häfele Loox5 profile 2102

- > Material: Plastic
- > Version: With drill mark for cable outlet
- Supplied with: 5 pairs of end caps

Colour	End cap 2102
Black	833.95.778
Brushed stainless steel coloured	833.95.779

Adhesive tape for Häfele Loox5 profile 2102



- > Area of application: For fixing aluminium on wood, metals, or plastics
- > Version: Double-sided, high instant adhesion, high temperature resistance
- > Length: 33 m
- > Width: 10 mm
- > Thickness: 0.6 mm

	Article No.
Adhesive tape	833.89.266




Profiles for surface mounting - Aluminium

Häfele Loox5 profile 2104, with concealed fixing



Häfele Loox5 profile 2104,
with asymmetric light distribution



End caps

- > Material: Profile: Aluminium, Diffuser: Plastic
- > Finish/colour: Profile: Anodized, Diffuser: White opal, transmittance 70–80 %
- > Length: 3000 mm
- > Diffuser width: 11 mm
- > Supplied with: 1 aluminium profile
1 diffuser white opal

Colour	Profile 2104
Black	833.95.739
Brushed stainless steel coloured	833.95.765



Order reference

Please order (mandatory) mounting bracket separately.



End caps for Häfele Loox5 profile 2104

- > Material: Plastic
- > Version: With drill mark for cable outlet
- > Supplied with: 5 pairs of end caps


Colour	End cap 2104
Black	833.95.784
Brushed stainless steel coloured	833.95.785




Diffusers
The diffuser creates a uniform light.
The LED points are invisible from 120 LEDs/m.
If required, please order alternative diffuser in black opal separately.



Diffusers see page 123



Mounting bracket for
concealed fixing




Mounting bracket

- > Material: Stainless steel
- > Mounting: For screw fixing
- > Supplied with: 5 pairs of mounting brackets

	Article No.
Mounting bracket	833.95.761

Profiles for surface mounting - Aluminium

Häfele Loox profile for surface mounting



End cap



Retaining clip

- > Material: Aluminium
- > Finish/colour: Silver coloured anodized
- > Length x width: 2500 x 18 mm
- > Height: 9.5 mm
- > Supplied with: 1 profile, 1 diffuser

Colour	Cat. No.
Silver coloured with milky diffuser	833.72.840



Note
LED points are always visible when this profile is used.
Permanent operation (≥8 hours/day) only with LED strip lights up to 9.6 W/m.



End cap for 833.72.840


- > Material: Plastic, silver coloured
- > Supplied with: 2 pieces

Colour	Cat. No.
Silver coloured	833.72.852

Retaining clip for 833.72.840

- > Material: Stainless steel, silver coloured
- > Supplied with: 2 pieces

Version	Cat. No.
Retaining clip	833.74.832



End cap



Retaining clip

- > Material: Aluminium
- > Finish/colour: Silver coloured anodized
- > Length x width: 2500 x 18 mm
- > Height: 14 mm
- > Supplied with: 1 profile, 1 diffuser

Colour	Cat. No.
Silver coloured with milky diffuser	833.72.841



End cap for 833.72.841

- > Material: Plastic
- > Supplied with: 2 pieces

Colour	Cat. No.
Silver coloured	833.72.853

Retaining clip for 833.72.841



- > Material: Stainless steel, silver coloured
- > Supplied with: 2 pieces

Version	Cat. No.
Retaining clip	833.74.832



Profiles for surface mounting - Aluminium

Häfele Loox profile for surface mounting, with attached diffuser housing



End cap Retaining clip

- > Material: Profile: Aluminium
Diffuser housing: Plastic
- > Finish/colour: Profile: Silver coloured anodized
Diffuser housing: Milky
- > Length x width: 2500 x 18 mm
- > Height: 18 mm
- > Supplied with: 1 aluminium profile
1 diffuser housing milky

Colour	Cat. No.
Silver coloured with diffuser housing	833.74.813

**End cap for 833.74.813**

- > Material: Plastic
- > Version: With cable outlet
- > Supplied with: 2 pieces

Colour	Cat. No.
Silver coloured	833.74.823

Retaining clip for 833.74.813

- > Material: Stainless steel
- > Application: For mounting as downlight
- > Supplied with: 2 pieces

Version	Cat. No.
Retaining clip	833.74.832


Häfele Loox corner profile



End cap



Holder



Mounting plate

- > Material: Aluminium
- > Finish/colour: Profile: Silver coloured anodized
Diffuser: Milky
- > Length x width: 2500 x 28 mm
- > Height: 20 mm
- > Supplied with: 1 aluminium profile
1 diffuser milky

Colour	Cat. No.
Silver coloured	833.74.812



**End cap and holder/ mounting plate**

- > Material: End cap and holder: Plastic, silver coloured; Mounting plate: Stainless steel
- > Supplied with: 2 pieces


	Cat. No.
End cap	833.74.822
Holder	833.74.825
Mounting plate	833.74.826

Profiles for surface mounting - Aluminium

Häfele Loox drawer profile



End caps



Retaining clip



Door Sensors

- > Material: Aluminium
- > Finish/colour: Profile: Silver coloured anodized
Diffuser: Milky
- > Length x width: 2500 x 18 mm
- > Height: 12.5 mm
- > Supplied with: 1 aluminium profile
1 diffuser milky

Colour	Cat. No.
Silver coloured	833.74.835



End cap set

- > Material: ABS plastic, silver coloured
- > Supplied with: 5 sets of end caps, fixing screws

	Cat. No.
End cap set	833.74.877

Retaining clip


- > Material: Stainless steel, silver coloured
- > Supplied with: 2 pieces

	Cat. No.
Retaining clip	833.74.893


	Cat. No.
Door sensors for Loox drawer profile (30W)	833.89.110

Profiles - Aluminium

Häfele Loox wardrobe rail, asymmetric light distribution



Rail end support, side panel



Wardrobe rail, rail centre support

- > Material: Aluminium
- > Finish/colour: Profile: Silver coloured anodized
Diffuser: Milky
- > Length x width: 2500 x 15 mm
- > Height: 30 mm
- > Supplied with: 1 aluminium profile
1 diffuser milky

Colour	Cat. No.
Silver coloured	833.72.790

LED points are always visible when this profile is used.

**Rail end support, side panel**

- > Material: Zinc alloy
- > Mounting: For screw fixing to side panel
- > Supplied with: 1 piece


	Cat. No.
Rail end support, side panel	803.33.757

Rail centre support, wardrobe rail

- > Material: Zinc alloy, chrome plated
- > Mounting: For screw fixing
- > Supplied with: 1 piece

	Cat. No.
Wardrobe rail, rail centre support	802.07.200

Häfele Loox glass edge profile



- > Material: Poly-carbonate
- > Finish/colour: Profile: Silver coloured
Diffusers: Milky
- > Length x width: 2000 x 17.5 mm
- > Height: 22 mm
- > Application: For screw fixing
- > Supplied with: 1 aluminium profile
2 diffusers milky

Colour	Cat. No.
Silver coloured	833.74.733





For manufacturing customised glass edge lighting for glass thicknesses of 4–8 mm.
Without load bearing function.
Only for LED strip lights with max. 9.6 W/m.
Note the dimensions of the clip connector.

Effect of the glass edge on the light

- > Glass edge with satin finish = even light line
- > Clear glass edge = point light

Profiles

Häfele two way aluminium profile



- > Material: Aluminium
- > Finish/colour: Silver coloured anodized
Diffuser: Milky
- > Length x width: 2500 x 50 mm
- > Height: 19 mm


Colour	Cat. No.
Silver coloured	833.01.720

Diffusers

Häfele Loox5 diffusers for profiles for recess mounting 1103 / 1104 / 1106 / 1107 as well as for profiles for surface mounting 2102 & 2104



Dimensions




- > Material: Plastic
- > Length: 3000 mm
- > Supplied with: 1 diffuser

Width mm	Transmittance black, ~25 %
8	833.95.758
11	833.95.759




The LED points are invisible from 120 LEDs/m. When using the black diffuser, LED points may be visible.

Replacement diffuser for Loox profiles with 16 mm internal dimension



Frosted

Milky



Diffuser version: Protruding, for push fitting

- > Material: Plastic
- > Length: 2500 mm
- > Supplied with: 1 diffuser

Diffuser	Frosted	Milky
Protruding, for push fitting	833.74.780	833.74.781



Diffuser version: Flush, for sliding in

- > Material: Plastic
- > Length: 2500 mm
- > Supplied with: 1 diffuser

Diffuser	Frosted	Milky
Protruding, flush for sliding in	833.72.858	833.72.859



- > Simple replacement of existing diffusers in order to switch from frosted to milky
- > Cannot be used for the following aluminium profiles: 833.74.812, 833.74.813 or for aluminium profiles with curved diffusers
- > Can be used only with Loox aluminium profiles



HÄFELE CONNECT BLE BOX



The Häfele Connect BLE box (Bluetooth low energy technology – ideal protocol for wireless light control) makes it possible to intuitively control furniture lighting and electrically operated fittings using a convenient app. A 12 V or 24 V driver supplies the BLE box via two leads. A single BLE Box or an entire network of BLE boxes is intuitively controlled via a Smartphone or tablet.

The Häfele Connect App makes it possible to control individual lights and electrically operated fittings.

The app controls the switching status (on/off), the brightness (0–100%) and also the colour temperature (with multi white lights) and the light colour (with RGB lights).


All parameters can be saved as scenarios and retrieved at any time.

Even time-controlled alteration of the brightness, the colour temperature, the light colour and the position of fittings is possible.

Real-life images of the actual room and the actual lights provide an intuitive operating experience. The Häfele Connect App is free for Apple IOS® and Android™.

	4 channel	
	BLE box 12 V	BLE box 24 V
Article No.:	850.00.005	850.00.006
Version	for on/off switching and dimming of lights (0–100%). Please order the BLE adapter separately for operating electrically operated fittings, RGB lights or multi white lights, see page 121.	
Number of connections	4	4
L x W x H (mm)	100 x 57 x 17	
Output current	2.5 A per output (max. 30 W with 12 V, max. 60 W with 24 V); sum total of all outputs max. 60 W with 12 V, max. 90 W with 24 V	
Standby power consumption (W)	<0.5 W	<0.6 W
Supplied with	1 BLE box, lead 300 mm	1 BLE box, lead 300 mm

HÄFELE CONNECT BLE BOX



- > The distance between the Smartphone or tablet to the nearest BLE box is approx. 10 m.
Multiple BLE boxes create a network, and can also be placed approx. 10 m apart.
- > One BLE box occupies 2 outputs of the driver.



BLE adapter for 4-channel BLE box

12 V

- > multi white, Article No.: 850.00.011
- > RGB, Article No.: 850.00.013

24 V

- > multi white: **850.00.012**



Switching

Sensor switches

Sensor switch
Door sensor switch
Motion detector
Dimmer
Captive switch/
dimmer
Sensor switch, surface
mounted



Sensor switch for aluminium profiles

Door sensor for drawer
profile




Mechanical switches

Universal door contact
switch
Door contact switch
Rocker switch
Housing for switch, surface
mounted



Multi switch box, multi driver box

Multi switch box
Multi driver box



Symbol overview

Sensor switch

Touchless, soft on/off
switching



Door sensor switch

Soft on/off switching




Motion detector

Automatic on/off switching



Dimmer

Soft on/off switching and
dimming



Captive switch/dimmer

Touchless on/off switching
and dimming



Universal door contact switch

On/off switching



Door contact switch

On/off switching,
door close = light off,
door open = light on



Rocker switch

On/off switching



Sensor switches


Häfele Loox sensor switch, modular – touchless, soft on/off switching


TOUCHLESS



- > Material/colour: Plastic, silver coloured
- > Degree of protection: IP20
- > Sensor range: 0–80 mm
- > Power consumption: ≤ 0.3 W
- > Drill hole Ø: 12 mm
- > Supplied with: 1 switch

	Cat. No.
Sensor switch, modular	833.89.127

-  Please order lead with snap-in connector for modular switches driver separately. Length 2 m: Cat. No. 833.89.142. See page 131


-  On/off state is stored without the need for power supply (memory function).

Häfele Loox door sensor switch, modular – soft on/off switching



- > Material/colour: Plastic, silver coloured
- > Degree of protection: IP20
- > Sensor range: 0–100 mm
- > Power consumption: ≤ 0.3 W
- > Drill hole Ø: 12 mm
- > Supplied with: 1 switch

	Cat. No.
Door sensor switch, modular	833.89.128


-  Please order lead with snap-in connector for modular switches driver separately. Length 2 m: Cat. No. 833.89.142. See page 131

Häfele Loox motion detector, modular – automatic on/off switching




- > Material/colour: Plastic, silver coloured
- > Degree of protection: IP20
- > Sensor range: 0–3000 mm
- > Sensor angle: 120 °
- > Power consumption: ≤ 0.1 W
- > Delay time: 30 sec.
- > Drill hole Ø: 12 mm
- > Supplied with: 1 motion detector

	Cat. No.
Motion detector, modular	833.89.129

-  Please order lead with snap-in connector for modular switches driver separately. Length 2 m: Cat. No. 833.89.142. See page 131

Sensor switches

Häfele Loox dimmer, modular – automatic on/off switching

WITH TOUCH/
TOUCHLESS

- > Material/colour: Plastic, silver coloured
- > Degree of protection: IP20
- > Power consumption: ≤ 0.3 W
- > Drill hole Ø: 12 mm
- > Supplied with: 1 dimmer

Type	Sensor range	Cat. No.
With touch	–	833.89.058
Touchless	0–60 mm	833.89.126



Please order lead with snap-in connector for modular switches driver separately. Length 2 m: Cat. No. 833.89.142. See page 131



Dimming value is stored without the need for voltage supply (memory function)

Häfele Loox capacitive switch/dimmer, modular – touchless on/off switching and dimming



- > Manual operation (proximity sensor), memory function
- > Concealed installation in wood, glass or stone (not in metalliferous materials) at a maximum depth of 30 mm
- > For screw fixing or recess mounting (drill hole Ø 35 mm)
- > A distance of min. 500 mm to electromagnetic fields (power lines, microwave) must be adhered to.

- > Material/colour: Plastic, silver coloured
- > Diameter: 35 mm
- > Height: 10 mm
- > Degree of protection: IP20
- > Power consumption: ≤ 1 W
- > Supplied with: 1 switch

	Cat. No.
Capacitive switch/dimmer, modular	833.89.133

This completely invisible operating solution opens up completely new possibilities in continuously adjustable light control.



Please order lead with snap-in connector for modular switches driver separately. Length 2 m: Cat. No. 833.89.142. See page 131


Sensor switches

Häfele Loox dimmer, surface mounted modular – soft on/off switching and dimming

WITH TOUCH



With touch function



- > Material/colour: Plastic, silver coloured
- > Dimension: 40 x 40 x 8.5 mm (L x W x H)
- > Degree of protection: IP20
- > Sensor range: 0–100 mm
- > Power consumption: ≤0.3 W
- > Supplied with: 1 switch with fixing material

	Cat. No.
Modular dimmer (with touch)	833.89.134



Please order lead with snap-in connector for modular switches driver separately. Length 2 m: Cat. No. 833.89.142. See page 131



Dimming value is stored without the need for voltage supply (memory function)

Häfele Loox door sensor for drawer profile



Door sensor

	Cat. No.
Door sensor for Loox drawer profile for 833.74.835	833.89.110

Mechanical switches

Häfele Loox universal door contact switch, modular – on/off switching



- > Material/colour: Plastic, black
- > Dimension: 51.8 x 40 x 14.2 mm (L x W x H)
- > Degree of protection: IP20
- > Supplied with: 1 switch with fixing material

	Cat. No.
Universal door contact switch, modular	833.89.143



Please order lead with snap-in connector for modular switches driver separately. Length 2 m: Cat. No. 833.89.142. See page 131



The universal door contact switch is suitable for hinged doors or single-leaf sliding doors.

Häfele Loox lead with snap-in connector for modular switches



- > Degree of protection: IP20
- > Supplied with: 1 lead

	Length mm	Cat. No.
Lead with snap-in connector for modular switches	1000 mm	833.89.141
	2000 mm	833.89.142




Required for modular switches



Drill hole Ø for plug: 12 mm

Häfele Loox door contact switch – on/off switching



- > Material/colour: Plastic, Black
- > Degree of protection: IP20
- > Drill hole Ø: 12 mm
- > Length: 28 mm
- > Supplied with: 1 switch with 2 m lead

	Cat. No.
Door contact switch	833.89.059



Drill hole Ø for plug: 12 mm

Mechanical switches

Häfele Loox rocker switch – on/off switching



- > Material/colour: Plastic, black
- > Diameter: 15 mm
- > Height: 17.7 mm
- > Drill hole Ø: 12 mm
- > Supplied with: 1 switch with 2 m lead

	Cat. No.
Rocker switch	833.89.106



Drill hole Ø for plug: 12 mm

Housing for switch, surface mounted



- > Dimension: 48 x 45 x 17 mm (L x W x H)
- > Diameter: 16 mm
- > Material/colour: Plastic, silver coloured
- > Supplied with: 1 housing
- > Application: For switch Ø 12 mm


	Cat. No.
Housing for switch	833.89.090



Suitable for 32 mm series drilled holes

Leads and Distributors

Extension leads 12 V / 24 V / 350 mA





> Supplied with: 1 lead

Length (mm)	Cat. No. (1000)	Cat. No. (2000)
12 V system, 3.5 A/20 AWG	833.73.765	833.73.766
24 V system, 3.5 A/20 AWG	833.77.713	833.77.714
350 mA system	833.80.705	833.80.706



For extending the connection leads of the LED lights.
> Lead length from driver to light max. 6 m

4-way extension lead – convenient extension for additional lights



> Length: 6,500 mm



> Supplied with: 1 lead

Application	Cat. No.
12 V system, 3.5 A/20 AWG	833.74.773
24 V system, 3.5 A/20 AWG	833.77.813



Makes it easier to power several lights positioned one after the other.
max. 4 lights per extension can be connected,
max. 2 extensions can be coupled

6-way distributor – for connecting additional lights to one driver





> Length x width: 58.5 x 34 mm
> Height: 18 mm
> Supplied with: 1 distributor with 2 m lead

Application	Cat. No.
12 V system, 3.5 A/20 AWG	833.74.798
24 V system, 3.5 A/20 AWG	833.77.724



With the 6-way distributor, up to 6 additional lights can be operated from one driver slot.

3-way distributor with switching function 12 V / 24 V



> Length x width: 57 x 34 mm
> Height: 18 mm
> Power consumption: 0.1 W
> Supplied with: 1 distributor with 200 m lead

Application	Wattage	Cat. No.
12 V system, 3.5 A/20 AWG	max. 42 W	833.74.751
24 V system, 3.5 A/20 AWG	max. 84 W	833.77.723



Up to 3 lights can be operated independently of the driver using the 3-way distributor with switching function connected to the output of the light.

Loox LED driver

Häfele Loox LED driver 12 V



Black

Wattage 20 W, 140 x 50 x 16 mm
Wattage 40 W, 190 x 60 x 16 mm
Wattage 60 W, 230 x 70 x 16 mm

833.74.960
833.74.962
833.74.913

- > Version: For up to 6 consumers
+ a switch with Loox plug system, without mains lead
- > Input voltage: 110–240 V, 50–60 Hz
- > Nominal voltage: DC 12 V



Häfele Loox LED driver 24 V



Black

Wattage 20 W, 140 x 50 x 16 mm
Wattage 40 W, 190 x 60 x 16 mm
Wattage 90 W, 190 x 60 x 16 mm

833.77.945
833.77.947
833.77.949

- > Version: For up to 6 consumers
+ a switch with Loox plug system, without mains lead
- > Input voltage: 110–240 V, 50–60 Hz
- > Nominal voltage: DC 24 V



Häfele Loox Mains lead 12/24 V, country-specific



Black, EU plug,
Length: 2 m

833.89.002

Häfele Loox Wall plug driver 12 V



Wall plug driver 15 W EU plug

Black

Wattage 6 W, 61 x 37 x 57 mm

833.74.933

Wattage 15 W, 78 x 46 x 68 mm

833.74.935

Wattage 27 W, 84 x 50 x 72 mm

833.74.937

Häfele Loox Lead 12 V



Black, 4 m lead
with 2 light slots

833.74.749



Black, 4 m lead
with 6-way distributor

833.74.748



Extending - Charging Stations

Häfele Loox ESC 2002 inductive charging station – for 12 V system



- > Material/colour: Plastic, matt black
- > Diameter: 64
- > Charging current: 1 A
- > Output voltage: 5 V
- > Standby power consumption: 0.3 W
- > Power consumption: Max. 10 W
- > Standard: WPC compatible
- > Supplied with: 1 inductive charging station with mounting ring and 2 m lead

Voltage		Cat. No.
12 V	ESC 2002 inductive charging station	833.73.776

⚠ Drill hole Ø for plug: 8 mm

🔌 12 V Loox 12 V driver see page 134

Häfele Loox ESC 2001 USB charging station, modular – for 12 V system



- > Material: Plastic, matt
- > Output voltage: 5 V
- > Output current: 2 A
- > Power consumption: Max. 15 W
- > Drill hole Ø: 35 mm
- > Mounting: For mounting in drilled hole, for clamp fixing
- > Supplied with: 1 USB charging station

Colour	Round
Black	833.73.751

➕ Lead with snap-in connector

mm	Cat.No
500	833.72.880
1000	833.72.881
2000	833.72.882

➡ Please order lead separately.

🔌 12 V Loox 12 V driver see page 134



Give your designs the perfect touch in the bath, vanity or closet areas with Häfele's Aquasys Range of Light Mirrors, consisting of the Aquasys, Aquasys X+ and Aquasys X Series. Beautifully designed, the mirrors add value, functionality and style to any interior space.

Aquasys Light Mirror - Multi-Functional Convenience



Bluetooth Capable Transducer System

- > Plays music from your mobile on the sound system integrated into the mirror



Demister (Mirror Heater)

- > Prevents the mirror from fogging up



Background Lighting

- > Functions as a source of mood and ambient lighting



Front Lighting

- > Offers adjustable lighting option from warm white to natural white


AQUASYS



The mirrors from the Aquasys Series are top-of-the-range models and come feature packed with the following:

- > Front Lighting
- > Background Lighting
- > Demister (Mirror heater)
- > Bluetooth Capable Transducer System
- > Application: Bathrooms

AQUASYS X+



The mirrors from the Aquasys X+ Series include mid-range models which have the following features:

- > Front Lighting
- > Background Lighting
- > Demister (Mirror heater)
- > Application: Bathrooms

AQUASYS X



The mirrors from the Aquasys X Series provide economical options for those looking for mirrors with:

- > Front Lighting
- > Background Lighting
- > Application: Dressing Rooms, Living Rooms & Bathrooms

Aquasys Light Mirror

SIZE VARIANTS & PRODUCT SPECIFICATIONS

①



900(W) X 600 (H) X 54 (D) mm

②



900(W) X 900 (H) X 54 (D) mm

③



1200(W) X 900 (H) X 54 (D) mm



600(W) X 900 (H) X 54 (D) mm

Please Note: The size variant can also be installed vertically



900(W) X 1200 (H) X 54 (D) mm

Article No.:	983.19.010 (Aquasys) 983.19.110 (Aquasys X+) 983.19.210 (Aquasys X)	983.19.020 (Aquasys) 983.19.120 (Aquasys X+) 983.19.220 (Aquasys X)	983.19.030 (Aquasys) 983.19.130 (Aquasys X+) 983.19.230 (Aquasys X)
Dimensions (W x H x D):	900 x 600 x 54 mm	900 x 900 x 54 mm	1200 x 900 x 54 mm
Colour Temperature:	Warm White (2700K) & Natural White (4000K)		
> Front Lighting:	Warm White (2700K) & Natural White (4000K)		
> Back Lighting:	Warm White (2700K)		
Front Lighting Lumen Output:			
> Warm White:	1080 Lm	1080 Lm	1560 Lm
> Cool White:	1230 Lm	1470 Lm	1764 Lm
Colour Rendering Index:	> 90	> 90	> 90
Wattage:	95 W	102 W	111 W
Lux @ 70 cm (luminous Flux / Area):	500		
Nominal Voltage:	DC 12 V		
Input Voltage:	100-240 V; 50-60 Hz		
Material:	LED Profile – Aluminium; Rear Back Plate – Wood		
Switch Type:	Touch LED Illuminated (Operation – Warm White, Stand-by – Blue)		
Demister (Mirror Heater):	Standby after 45 minutes (only applicable for Aquasys and Aquasys X+ Mirrors)		
Sound System:	Bluetooth Transducer System; Password – 0000 (only applicable for Aquasys Mirrors)		
Bluetooth Frequency:	2.4 GHz (only applicable for Aquasys Mirrors)		
Degree of Protection:	IP 44 (Splash-proof for use in wet rooms)		
Warranty:	2 Years		
Energy Efficiency Class:	A		
Certification	BIS/ UL / CUL / SAA / CE / TÜV certified as per EN 1036-1:2007 against corrosion resistance		



Series Name	Article No	Dimensions (W×H×D) mm	Net Weight Kg.	Front Lighting	Background Lighting	Demister Mirror Heater	Bluetooth Capable Transducer System
Aquasys	983.19.010	900 × 600 × 54	10.82	•	•	•	•
Aquasys	983.19.020	900 × 900 × 54	14.88	•	•	•	•
Aquasys	983.19.030	1200 × 900 × 54	19.38	•	•	•	•
Aquasys X+	983.19.110	900 × 600 × 54	9.70	•	•	•	
Aquasys X+	983.19.120	900 × 900 × 54	13.30	•	•	•	
Aquasys X+	983.19.130	1200 × 900 × 54	18.00	•	•	•	
Aquasys X	983.19.210	900 × 600 × 54	9.40	•	•		
Aquasys X	983.19.220	900 × 900 × 54	13.00	•	•		
Aquasys X	983.19.230	1200 × 900 × 54	17.50	•	•		

420 E Sound system

Bluetooth® receiver with exciter speaker



Invisible sound system with impressive quality on many different surfaces.

Quick and easy installation, therefore also ideal for retrofitting.

- > Power consumption: During operation with 2 exciter speakers: Max. 19 W, during optional operation with 4 exciter speakers: Max. 32 W
- > Reception range: Max. 10 m
- > Nominal voltage: 110–240 VAC
- > Power connection: With 2 m lead to 12 V driver
- > Dimensions: 140 x 45 x 15 mm
- > Installation: For screw fixing
- > Exciter version: Speaker for screw or glue fixing with 1 m lead



Including 2 exciter speakers. Expansion to 4 exciter speakers possible.

Available on request: Multi-room control for separating different users in adjacent rooms.



LED driver 12 V

► page 134

420 E Sound system

420 E Sound system with 2 exciter speakers
Exciter speaker

822.65.034
822.65.039

Pop-Up-Sockets

Pop-up Socket



Less is indeed more! Functionality at a pull. Häfele integrates concepts of space efficiency, functionality, ease, entertainment and advanced technology seamlessly into its New Pop-up Socket Systems.

- > Effective utilisation of space
- > Reduces dependency on the traditional wall socket systems:
- > Packs-in a unique dose of entertainment through the integrated Bluetooth audio system.
- > Is splash-proof (IP54 in a close position) which means that it is resistant to water splashing from all directions

Type	Dimensions (mm)	No. of Sockets	Input	Cat. No.
Pop-up Socket with Bluetooth Speaker	430 x Ø100	10A universal socket x 2 USB socket (Max.2100mA) x 2 Bluetooth audio system x 1 On/Off neon switch x 1 2 meter cable with SA plug	220 – 240 V ~ 50 Hz	822.80.900
Pop-up Socket without Bluetooth Speaker	430 x Ø100	10A universal socket x 2 USB socket (Max.2100mA) x 2 On/Off neon switch x 1 2 meter cable with SA plug	220 – 240 V ~ 50 Hz	822.80.901



Movable Walls &
Autotec Automatic

PAGE

143

Movable Walls / Autotec Automatic – Product overview

PALACE 80



> page 146

TRANSPALACE




> page 147

PALACE 90



> page 148

PALACE 110 S



> page 149

PRESIDENT



> page 150

AUTOTEC AUTOMATIC



> page 151

All you need to know about Movable Walls

Movable walls allow business owners and homeowners to create the floor plan they need out of a wide-open space. Movable walls are partitions that can increase the functionality of an open area such as a loft apartment, warehouse, conference room or banquet hall. These systems can provide privacy and good acoustic insulation for work and living environments.

Uses:

Movable wall panels are an ideal way to separate areas and create privacy in a room.

- Homeowners can select wall panels that create a solid wall and door for entry into a bedroom or living area or use glass panels to define separate areas of the living space while keeping the open floor concept in the room.
- In a business environment, movable walls are a quick way to set up offices and change the layout of the building space to accommodate new workers.

- Hotels and Malls can use movable walls to create more number of functional areas within the available space – for instance, a banquet hall or a convention centre in a Hotel can double up with a movable wall partition to accommodate two functions or conferences simultaneously.

Movable Wall Systems by Hafele:

Hafele brings to you its range of Movable Wall systems from Parthos, Netherlands. These systems are ideal for uniting or dividing spaces within a given area to achieve optimal space utility. Our range of movable wall systems gives you the flexibility of customization and conforms to the highest standards of functionality and quality.

Our products help to expand the imagination of designers. This applies especially to the development of flexible space-saving solutions for hotels, congress and convention centres, schools, restaurants, shopping centres, commercial buildings or large apartments.

Our greatest strength is our ability to deliver custom work.



Palace 80




For many types of users, the Palace 80 may very well be the ultimate solution for creating more space and flexibility.

This movable wall with a panel thickness of only 80 mm will guarantee an optimal ease of operation with only the slightest loss of space. The favourable cost aspect also makes it an excellent alternative. Furthermore, the Palace 80 proves that a slim construction does not affect the stability and sound insulation.

The trolleys of this wall are suspended on metal bearers running horizontally through the panel. The result is a self supporting structure.

- > Panel Thickness: 80MM
- > Panel Height: 1500-3500MM
- > Panel width: 600 - 1240MM
- > Frame construction: Aluminium / Wood
- > Board Material: 9MM, carried by the construction
- > Fire Safety: Optional fire-retardant class B1/M1
- > Vertical profile: Aluminium, Anodized, with sealing profiles
- > Pressure Sleeves: Aluminium, Black with double sealing profiles
- > Operation of pressure sleeves: Manual
- > Doors: Single door in panel or fixed single door
- > Sound installation: 40 and 44 DB RW
- > Weight (depending on sound insulation value): approx: 40 & 44 kg/m²
- > Standard version with covering profiles
- > Very easy to operate due to light construction
- > High-quality track and trolley system
- > Stable and self-supporting frame construction
- > Enormous flexibility thanks to a broad range of panels

Transpalace



The most exclusive model in the Palace series is the Transpalace. This sturdy, transparent movable wall has been finished with double-layer safety glass. Transpalace will allow you to retain the transparency,

while enjoying what the other Palace walls have to offer, such as a high degree of sound insulation, a stable frame and a beautiful design. The technology has been subtly incorporated behind a thin panel of glass, in the colour of your choice.

- > Panel Thickness: 80/100MM
- > Panel Height: 1500-3500MM
- > Panel width: 600 - 1240MM
- > Frame construction: Aluminium
- > Board Material: 10MM, safety-glass carried by the construction
- > Fire Safety: Optional fire-retardant glass
- > Vertical profile: Aluminium, Anodized, with sealing profiles
- > Pressure Sleeves: Aluminium, Black with double sealing profiles
- > Operation of pressure sleeves: 80: Manual / 100: Electrical
- > Doors: Single door in panel or fixed single door
- > Sound installation: 44 and 46 DB RW
- > Weight (depending on sound insulation value): approx: 65 kg/m²
- > Glass Can Be Replaced Separately
- > Aluminium Profiles, Available In Every Ral Colour Chart System
- > Slim Glass Available In Every Colour
- > Welded Aluminium/Steel Construction


Palace 90



The Palace 90 is a paradigm of robust custom work. In spite of its slim look, the Palace 90 disposes of an extensive package of functional characteristics. Furthermore, this type of wall is suited to every (working) environment. The inlaid aluminium border profiles give it an especially stylish look.

- > Panel Thickness: 90MM
- > Panel Height: 1500-4000MM
- > Panel width: 600 - 1240MM
- > Frame construction: Aluminium / Wood
- > Board Material: 8MM, carried by the construction
- > Fire Safety: Optional fire-retardant class B1/M1
- > Vertical profile: Aluminium, Anodized, with sealing profiles invisible when wall is closed
- > Pressure Sleeves: Aluminium, Black with double sealing profiles
- > Operation of pressure sleeves: Manual
- > Doors: Single door in panel or fixed single door
- > Sound installation: 46 and 48 DB RW
- > Weight (depending on sound insulation value): approx: 32-50 kg/m²
- > New EPDM pressure sleeve and pieces for improved acoustic properties
- > Standard version with inlaid profiles
- > Stable and self-supporting frame construction
- > Enormous flexibility thanks to a broad range of panel models
- > Attractively priced
- > Very easy to operate
- > High-quality track and trolley system

Palace 110 S



The Palace 110 makes it much easier to organise your space: a high degree of sound insulation, single or double doors, height of more than fifteen metres, curved panels if required, semi-automatic operation and fire resistance rating of up to sixty minutes!

- > Panel Thickness: 110MM
- > Panel Height: 1500-15000MM
- > Panel width: 600 - 1240MM
- > Frame construction: Aluminium / Steel
- > Board Material: 16MM, carried by the construction
- > Fire Safety: Optional fire-retardant class B1/M1
- > Vertical profile: Aluminium, Anodized, with magnetic strips and sealing profiles
- > Pressure Sleeves: Aluminium, Black with double sealing profiles
- > Operation of pressure sleeves: Manual or Electrical
- > Doors: Single door in panel or fixed single door
- > Sound installation: 45, 50, 53, 56, 57, 58 DB RW
- > Weight (depending on sound insulation value): approx: 31-56 kg/m²
- > Durable and stable metal construction
- > Possible heights of more than 15 metres
- > Optimal flexibility, curved walls and tracks possible
- > Available in a fire-resistant model of up to 30 and 60 minutes with passdoor
- > Available in a broad range of finishes
- > High-quality track and trolley system
- > L- shaped semi-automatically operated top & bottom seals possible


President



An enormous degree of user-friendliness and an extensive range of options as to design and finish are among the President's greatest advantages. In addition to design, we also pay a great deal of attention to user-friendliness.

- > Completely transparent partition
- > Curved segmented models available
- > Virtually unlimited choice of options in pattern and design
- > High-quality track and trolley system
- > Extremely durable clamping construction without necessity of drilling the glass
- > Profiles and track available in several colours

Autotec Automatic Doors



Hardware Specification:

- > High load capacity up to 125 kg
- > Door thickness 12 mm
- > Automatic sliding system for internal glass doors
- > Comes configured with an energy saving system which leads to lower power consumption (less than 0.5 W)
- > Boasts of 70% less electricity consumption
- > Highest level of safety – EN16005 standard
- > Cycle testing: 10,00,000 cycles

Features :

- > The system has a smooth and silent operation due to the roller and track mechanism
- > Different configurations (modes) are available as per the application desired
- > In case of power failure, there is an option of battery backup
- > IP54 rated - Limited dust ingress and protection against water spray (canopy is required if the system is exposed to the external environment)

Autotec Automatic Doors

935.06.000

Assembly Kit for Drive

Autotec Automatic Doors

935.06.001

Additional Assembly Kit for Double doors

Autotec Automatic Doors

ACCESSORIES

Product Name	Article No.
Accessory for sensor installed on the cover	935.06.021
Rubber for operator	935.06.022
Assembly kit for lateral cover L+R SL300	935.06.023
BELT	935.06.039
HR100CT active IR motion and presence sensor	935.06.083
Microwave movement sensor Hr-50	935.06.084
COM 20 for advanced module selector	935.06.082
Autotec glass clamp offset	941.10.100
SS Clamp for Sly glass rollers	941.10.020
OPTIONAL	
Battery BU3	935.06.019
ES lock EL5	935.06.018



BOM LIST	
Description	Article No.
Single door kit with 4.28 track with lock & battery, mode selector with a touch screen (COM 20)	935.06.106
Double door kit with 4.28 track with lock & battery, mode selector with a touch screen (COM 20)	935.06.107
Double door kit with 6.28 track with lock & battery, mode selector with a touch screen (COM 20)	935.06.108
Single door kit with 4.28 track with lock & battery, mode selector with a touch screen (COM 20) and double side safety sensor- HR100CT	935.06.109
Double door kit with 4.28 track with lock & battery, mode selector with a touch screen (COM 20) and double side safety sensor- HR100CT	935.06.110
Double door kit with 6.28 track with lock & battery, mode selector with a touch screen (COM 20) and double side safety sensor- HR100CT	935.06.111



Surfaces

PAGE

153

Surfaces - Product Overview

SURFACES - CEASERSTONE



> page 155

SURFACES - DEKTON



> page 158


Surfaces - Ceaserstone



Classico™

Surfaces For Your Home

Caesarstone's Classico™ collection combines style and functionality with colours and designs ideal for numerous applications in both residential and commercial interiors such as kitchen benchtops, splashbacks, bathroom wall linings, custom made furniture and more.

Pure White **562.60.575**Concrete **562.60.087**Snow **562.60.067**White Shimmer **562.60.555**Raven **562.00.006**Buttermilk **562.60.595**Shitake **562.60.157**Ginger **562.60.665**Mink **562.60.137**Wild Rice **562.60.645**Organic White
562.60.177Ice Snow **562.60.277**Oyster **562.00.026**Frozen Terra
562.59.264Piatto Black
562.59.424Ocean Foam
562.59.326


Surfaces - Ceasarstone

Supernatural™
The One of a Kind Collection


Just like an original work of art, every Supernatural slab is one of a kind a quartz surface that will take your interior décor to a whole new level. Mirroring nature's endless diversity and beauty, each slab is finished to perfection.

Inspired by some of the world's most beautiful natural marble, Caesarstone's supernatural designs represent the very best of what nature has to offer. Using cutting-edge technology, these earthy tones and delicate veins are infused with intricacies and textures never before seen on quartz surfaces.


The new Supernatural designs adorn any modern interior, while maintaining all the advantages and timeless qualities that make Caesarstone special.



London Grey
562.60.625




Piatra Grey
562.60.197



Vanilla Noir
562.60.545




Alpine Mist
562.60.357



Frosty Carrina
562.60.685



Dreamy Marfil
562.60.605



Coastal Grey
562.60.727



Bianco Drift
562.60.377




Statuario Maximus*
562.60.497



Georgian Bluffs
562.59.046




Moorland Fog
562.59.016




White Attica
562.59.076



Turbine Grey
562.59.056



Empira White
562.60.814



Woodlands
562.59.434



Montblanc
562.59.860

Surfaces - Ceaserstone



Metropolitan™ The Metropolitan Collection is a unique collection leading the urban interior trend. The Metropolitan Collection reflects the authentic textures of manufacturing, such as oxidized steel, poured plaster and raw concrete. These unpolished designs reveal variations in appearance and capture depth and movement throughout the surface. Caesarstone's new cutting-edge technology achieves a weathered patina in quartz never experienced before.



Rugged Concrete
562.59.006



Cloudburst Concrete
562.59.858



Topus Concrete
562.59.873




Airy Concrete
562.59.874



Excava **562.59.294**



Primordia
562.60.815



Black Tempal
562.59.394




Oxidian **562.59.414**

Surfaces - Dekton




Outdoor Countertops:


When designing an outdoor surface we need to take gravity into account: everything floating in the air will end up falling onto it. And it can be unused for weeks and months. A strong material with high resistance to UV-rays, thermal fluctuations, Scratches and stains would be your best bet in such applications. Sounds hypothetical? Not really. Dekton surfaces come with the ideal properties to sustain the harsh conditions of outdoor applications and thus become your ideal choice for countertops that need to be installed outside your home. The myriad choice of finishes and designs available in this range can help you create a unique application, just the kinds you had always imagined.




Entzo **562.58.146**




Aura 15 **562.58.126**




Spectra **562.58.246**




Splendor **562.58.266**




Blaze **562.58.276**




Halo **562.58.206**




Lumina **562.58.256**



Glacier **562.58.216**



Tundra **562.58.236**







Fiord **562.58.226**

Surfaces - Dekton

**Wall Cladding:**

Gone are the days when your kitchen and dado walls hide behind plastered paints, inconsistent tiles or dull wall papers. Dekton's unique surface properties like low water absorption and fire resistance make it an ideal choice for wall cladding applications in kitchens as well as the other areas of your interior spaces. Moreover the dimensional stability provides an overall consistency in design making for a seamless look without borders or differences. The end result is a surface that adorns your walls with spectacular aesthetics as well as robust and ever-lasting durability

Domoos **562.58.006**Vegha **562.58.056**Kadum **562.58.036**Sirocco **562.58.016**Danae **562.58.156**Sirius **562.58.306**Strato **562.58.026**Ventus **562.58.086**Galema **562.58.076**Gada **562.58.316**Keranium **562.58.046**Keon **562.58.106**

Surfaces - Dekton




Flooring and Indoor Countertops:

The aesthetic appeal of any kitchen is greatly emphasized by the choice of countertops and flooring materials used. Today, the need to move away from clinical and functional designs is changing the spectrum of material choices available in the market. Dekton, with its unique material properties, forms an ideal choice for every surface in your kitchen – be it countertops, flooring or even cabinet fronts. It's scratch and stain resistance properties along with low water absorption levels make it a robust choice for countertops and floorings. The spectrum of designs and patterns available through Dekton, bring with it the flexibility to design your kitchen your way – you may choose to follow a seamless synergy between the flooring, cabinets and countertops or else bring in a healthy contrast of tones.



Trilium **562.58.196**




Kelya **562.58.066**



Makai **562.58.346**



Orix **562.58.186**



Zenith **562.58.116**




Radium **562.58.096**



Kira **562.58.446**



Nilium **562.58.455**



Kairos **562.58.136**




Vera **562.58.426**


Surfaces - Dekton




Opera **562.58.435**




Laurent **562.58.416**




Bromo **562.58.496**




Milar **562.58.506**



Laos **562.58.516**




Portum **562.58.526**




Bedrock **562.58.536**



Feroe **562.58.546**



Baltic **562.58.556**



Soke **562.58.488**

IMPRINT

This catalogue is only intended for use by the recipient.
All constituents of the catalogue are the property of Hafele.

Reprint of the catalogue or extracts thereof, reprinting or imitation
of the illustrations or imitation of the design is forbidden.

The technical representations and dimensional information in this
catalogue are non-binding, including those in the illustrations and
drawings. Right reserved to make design improvements.
All dimensions in mm unless otherwise specified.

No liability accepted for printing errors and mistakes made during
the production of the catalogue.

All deliveries will be made in accordance with Hafele terms and
conditions of sale.

Issued by:
Hafele India Pvt. Ltd.
Office No. 3, Building "A", BETA, I Think Techno Campus,
Off J.V.L.R, Opp. Kanjurmarg Station, Kanjurmarg East,
Mumbai - 400 042. INDIA.

Tel.: +91 22 6142 6100
Fax: +91 22 6695 0922

Internet: www.hafeleindia.com
Email: customercare@hafeleindia.com

June 2020.
© by Hafele India.
All rights reserved.

**Mumbai Design Centre:**

Haji Moosa Patrawala Ind.(SOBO)
Estate, Near Famous Studio,
Mahalaxmi (West), Mumbai - 400 011
Tel.: 022 6264 7100.

Mumbai Design Centre:

#2 Filix Building, Opp. Asian Paints,
L.B.S. Marg, Bhandup (West),
Mumbai - 400 078
Tel.: 022 2596 9660/
2596 9787/2594 7305

New Delhi Office & Design Centre:

D-89 , 1st Floor, Okhla Phase-I,
New Delhi - 110 020
Tel.: 011-66574999
Fax: 011-41605482

Bangalore Office & Design Centre:

Incubex Nestavera Spaces Pvt Ltd,
No:13, Langford Place, Langford Road,
Shanti Nagar, Bangalore - 560 025
Tel.: 080 4132 6116
Fax: 080 4132 6226

Bangalore**Hafele Appliances Gallery:**

No. 2/1, Shiv Manor, Langford Road,
Shantinagar, Bangalore - 560027
Tel.: 080 - 4142 6336

Sri Lanka:**Hafele Office and Design Centre:**

52, Nandana Gardens
(On Duplication Road), Colombo 04.
Tel: +94 112 500 501.
Fax: 0094 112 500 553.

Hafele Design Centre:

448, Galle Road, Rawathawatta,
Moratuwa, Sri Lanka.
Tel.: +94 112 644 600.

Hafele Boutique:

747A, Sirimawo Bandaranayaka
Mawatha, Mulgampola,
Kandy, Sri Lanka.
Tel.: +94 812 223 338.

Hyderabad Office & Design Centre:

SJR Building - # 1-57/89/1 & 1-57/89/2
Opp Allahabad Bank, Gachibowli,
Hyderabad – 500032
Tel.: 040 29557578 / 040 29557588

Kolkata Design Centre:

PS PACE, Premises No. 1/1A,
Mahendra Roy Lane, Topsia,
Kolkata - 700 046
Tel.: 033 40086814 / 033 40089268
Fax: 033 24988020

Kolkata Office:

Office No. 1001, PS Continental,
10th Floor, 83/2/1 Topsia Road,
Near Vishwakarma Building.
South Kolkata - 700046
Tel: 033-2285 0104 /
033-2285 0105 / 033-2285 0106

Chennai Office & Design Centre:

1st Floor No.24, College Road,
Nungambakkam, Chennai - 600 006
Tel.: 044 - 4215 1542
Fax: 044 2446 0922

Bangladesh Office:

2nd Floor, House - 181, Road - 2,
Mohakhali DOHS, Dhaka - 1206.
Tel.: 01844018431/ 01844018432/
01844018433/ 01844018437.

Bangladesh Design Center:

House - 106, Road - 12,
Block - E, Banani, Dhaka - 1213
Tel.: 02-48810380-81

Nepal:

UHS Holdings Pvt. Ltd.
Kathmandu-2,
Gairidhara Chowk, Nepal.
Mob.: +977 9802338800

Pune Design Centre:

Showroom No. 2, Ground Floor,
F P no. 403, A/2, ICC Trade Tower,
Senapati Bapat Marg,
Shivaji Nagar, Pune -411016
Tel.: 020 2563 3301
Fax: 020 2563 3302

Pune Office:

Office No. 12, Vastushree Complex,
Survey No.587,
Near Hyde Park, Gultekdi,
Market Yard, Pune - 411 037
Tel.: 020 2426 6264
Fax: 020 2426 6274

Ahmedabad Office:

Hafele India Pvt. Ltd., Office No. 302,
3rd Floor, Shangrila Arcade, Near
Shyamal Cross Road, Satellite,
Ahmedabad - 380015
Tel.: +91 79695 55505 / 8866220505

Cochin Office:

Jomer Symphony, 5th Floor, 48/1744
C34, Chalikkavattom, North Ponnuranni,
Vyttila, Cochin- 682010

Bhutan:

Smart Homes
Gr. Floor, Druk Building (Opp Helipad)
Babesa -Thimpu Expressway, Thimpu
Tel.: +975-2-333419
Mob.: +975-77277615, 17839717,
77114228,1760063,17669840

**Mumbai Corporate Office:**

Office No. 3, Building "A", BETA,
I Think Techno Campus, Off J.V.L.R.,
Opp. Kanjurmarg East, Mumbai – 400 042.
Tel.: 022 6142 6100 | Fax: 022 6702 0531.

For Enquiries SMS "HÄFELE" to 56070

Toll Free Customer Care: 1800 266 6667
Customer Care WhatsApp: +91 97691 11122
customer care@hafeleindia.com
info@hafeleindia.com

Follow us on

